
Symbolic Logic

Release 10.6

The Sage Development Team

Jun 27, 2025

CONTENTS

1	Propositional Calculus	1
2	Boolean Formulas	9
3	Evaluation of Boolean Formulas	35
4	Module that creates and modifies parse trees of well formed boolean formulas.	39
5	Symbolic Logic Expressions	51
6	Logic Tables	63
7	Indices and Tables	67
	Python Module Index	69
	Index	71

PROPOSITIONAL CALCULUS

Formulas consist of the following operators:

- $\&$ – and
- $|$ – or
- $\sim$ – not
- $\wedge$ – xor
- $\rightarrow$ – if-then
- $\leftrightarrow$ – if and only if

Operators can be applied to variables that consist of a leading letter and trailing underscores and alphanumerics. Parentheses may be used to explicitly show order of operation.

AUTHORS:

- Chris Gorecki (2006): initial version, propcalc, boolformula, logictable, logicparser, booleval
- Michael Greenberg – boolopt
- Paul Scurek (2013-08-05): updated docstring formatting
- Paul Scurek (2013-08-12): added `get_formulas()`, `consistent()`, `valid_consequence()`

EXAMPLES:

We can create boolean formulas in different ways:

```
sage: f = propcalc.formula("a & ((b | c) ^ a -> c) <-> b")
sage: g = propcalc.formula("boolean <-> algebra")
sage: (f & ~g).ifthen(f)
((a & ((b | c) ^ a -> c) <-> b) & (~ (boolean <-> algebra))) -> (a & ((b | c) ^ a -> c) <-> b)
```

```
>>> from sage.all import *
>>> f = propcalc.formula("a & ((b | c) ^ a -> c) <-> b")
>>> g = propcalc.formula("boolean <-> algebra")
>>> (f & ~g).ifthen(f)
((a & ((b | c) ^ a -> c) <-> b) & (~ (boolean <-> algebra))) -> (a & ((b | c) ^ a -> c) <-> b)
```

We can create a truth table from a formula:

```
sage: f.truthtable()
a      b      c      value
False  False  False  True
```

(continues on next page)

(continued from previous page)

```

False False True True
False True False False
False True True False
True False False True
True False True False
True True False True
True True True True
sage: f.truthtable(end=3)
a      b      c      value
False False False True
False False True True
False True False False
sage: f.truthtable(start=4)
a      b      c      value
True False False True
True False True False
True True False True
True True True True
sage: propcalc.formula("a").truthtable()
a      value
False False
True True

```

```

>>> from sage.all import *
>>> f.truthtable()
a      b      c      value
False False False True
False False True True
False True False False
False True True False
True False False True
True False True False
True True False True
True True True True
>>> f.truthtable(end=Integer(3))
a      b      c      value
False False False True
False False True True
False True False False
>>> f.truthtable(start=Integer(4))
a      b      c      value
True False False True
True False True False
True True False True
True True True True
>>> propcalc.formula("a").truthtable()
a      value
False False
True True

```

Now we can evaluate the formula for a given set of input:

```
sage: f.evaluate({'a':True, 'b':False, 'c':True})
False
sage: f.evaluate({'a':False, 'b':False, 'c':True})
True
```

```
>>> from sage.all import *
>>> f.evaluate({'a':True, 'b':False, 'c':True})
False
>>> f.evaluate({'a':False, 'b':False, 'c':True})
True
```

And we can convert a boolean formula to conjunctive normal form:

```
sage: f.convert_cnf_table()
sage: f
(a|~b|c)&(a|~b|~c)&(~a|b|~c)
sage: f.convert_cnf_recur()
sage: f
(a|~b|c)&(a|~b|~c)&(~a|b|~c)
```

```
>>> from sage.all import *
>>> f.convert_cnf_table()
>>> f
(a|~b|c)&(a|~b|~c)&(~a|b|~c)
>>> f.convert_cnf_recur()
>>> f
(a|~b|c)&(a|~b|~c)&(~a|b|~c)
```

Or determine if an expression is satisfiable, a contradiction, or a tautology:

```
sage: f = propcalc.formula("a|b")
sage: f.is_satisfiable()
True
sage: f = f & ~f
sage: f.is_satisfiable()
False
sage: f.is_contradiction()
True
sage: f = f | ~f
sage: f.is_tautology()
True
```

```
>>> from sage.all import *
>>> f = propcalc.formula("a|b")
>>> f.is_satisfiable()
True
>>> f = f & ~f
>>> f.is_satisfiable()
False
>>> f.is_contradiction()
True
>>> f = f | ~f
```

(continues on next page)

(continued from previous page)

```
>>> f.is_tautology()
True
```

The equality operator compares semantic equivalence:

```
sage: f = propcalc.formula("(a|b)&c")
sage: g = propcalc.formula("c&(b|a)")
sage: f == g
True
sage: g = propcalc.formula("a|b&c")
sage: f == g
False
```

```
>>> from sage.all import *
>>> f = propcalc.formula("(a|b)&c")
>>> g = propcalc.formula("c&(b|a)")
>>> f == g
True
>>> g = propcalc.formula("a|b&c")
>>> f == g
False
```

It is an error to create a formula with bad syntax:

```
sage: propcalc.formula("")
Traceback (most recent call last):
...
SyntaxError: malformed statement
sage: propcalc.formula("a&b~(c|(d)")
Traceback (most recent call last):
...
SyntaxError: malformed statement
sage: propcalc.formula("a&&b")
Traceback (most recent call last):
...
SyntaxError: malformed statement
sage: propcalc.formula("a&b a")
Traceback (most recent call last):
...
SyntaxError: malformed statement
```

It is also an error to not abide by the naming conventions.

```
sage: propcalc.formula("~a&9b")
Traceback (most recent call last):
...
NameError: invalid variable name 9b: identifiers must begin with a letter and contain
↳ only alphanumerics and underscores
```

```
>>> from sage.all import *
>>> propcalc.formula("")
Traceback (most recent call last):
...
```

(continues on next page)

(continued from previous page)

```

SyntaxError: malformed statement
>>> propcalc.formula("a&b~(c|(d) ")
Traceback (most recent call last):
...
SyntaxError: malformed statement
>>> propcalc.formula("a&b&b")
Traceback (most recent call last):
...
SyntaxError: malformed statement
>>> propcalc.formula("a&b a")
Traceback (most recent call last):
...
SyntaxError: malformed statement

It is also an error to not abide by the naming conventions.
>>> propcalc.formula("~a&9b")
Traceback (most recent call last):
...
NameError: invalid variable name 9b: identifiers must begin with a letter and contain
↳only alphanumerics and underscores

```

sage.logic.propcalc.**consistent** (**formulas*)

Determine if the formulas are logically consistent.

INPUT:

- **formulas* – instances of BooleanFormula

OUTPUT: a boolean value to be determined as follows:

- True – if the formulas are logically consistent
- False – if the formulas are not logically consistent

EXAMPLES:

This example illustrates determining if formulas are logically consistent.

```

sage: f, g, h, i = propcalc.get_formulas("a<->b", "~b->~c", "d|g", "c&a")
sage: propcalc.consistent(f, g, h, i)
True

```

```

>>> from sage.all import *
>>> f, g, h, i = propcalc.get_formulas("a<->b", "~b->~c", "d|g", "c&a")
>>> propcalc.consistent(f, g, h, i)
True

```

```

sage: j, k, l, m = propcalc.get_formulas("a<->b", "~b->~c", "d|g", "c&~a")
sage: propcalc.consistent(j, k, l, m)
False

```

```

>>> from sage.all import *
>>> j, k, l, m = propcalc.get_formulas("a<->b", "~b->~c", "d|g", "c&~a")
>>> propcalc.consistent(j, k, l, m)
False

```

AUTHORS:

- Paul Scurek (2013-08-12)

`sage.logic.propcalc.formula(s)`

Return an instance of `BooleanFormula`.

INPUT:

- `s` – string that contains a logical expression

OUTPUT: an instance of `BooleanFormula`

EXAMPLES:

This example illustrates ways to create a boolean formula:

```
sage: f = propcalc.formula("a~b|c")
sage: g = propcalc.formula("a^c<->b")
sage: f&g|f
((a&~b|c) & (a^c<->b)) | (a&~b|c)
```

```
>>> from sage.all import *
>>> f = propcalc.formula("a~b|c")
>>> g = propcalc.formula("a^c<->b")
>>> f&g|f
((a&~b|c) & (a^c<->b)) | (a&~b|c)
```

We now demonstrate some possible errors:

```
sage: propcalc.formula("( (a&b) ")
Traceback (most recent call last):
...
SyntaxError: malformed statement
sage: propcalc.formula("_a&b")
Traceback (most recent call last):
...
NameError: invalid variable name _a: identifiers must begin with a letter and
↳ contain only alphanumerics and underscores
```

```
>>> from sage.all import *
>>> propcalc.formula("( (a&b) ")
Traceback (most recent call last):
...
SyntaxError: malformed statement
>>> propcalc.formula("_a&b")
Traceback (most recent call last):
...
NameError: invalid variable name _a: identifiers must begin with a letter and
↳ contain only alphanumerics and underscores
```

`sage.logic.propcalc.get_formulas(*statements)`

Convert statements and parse trees into instances of `BooleanFormula`.

INPUT:

- `*statements` – strings or lists; a list must be a full syntax parse tree of a formula, and a string must be a string representation of a formula

OUTPUT: the converted formulas in a list

EXAMPLES:

This example illustrates converting strings into boolean formulas.

```
sage: f = "a&(~c<->d) "
sage: g = "d|~b"
sage: h = "~(a->c)<->(d|~c) "
sage: propcalc.get_formulas(f, g, h)
[a&(~c<->d), d|~b, ~(a->c)<->(d|~c)]
```

```
>>> from sage.all import *
>>> f = "a&(~c<->d) "
>>> g = "d|~b"
>>> h = "~(a->c)<->(d|~c) "
>>> propcalc.get_formulas(f, g, h)
[a&(~c<->d), d|~b, ~(a->c)<->(d|~c)]
```

```
sage: A, B, C = propcalc.get_formulas("(a&b)->~c", "c", "~(a&b) ")
sage: A
(a&b)->~c
sage: B
c
sage: C
~(a&b)
```

```
>>> from sage.all import *
>>> A, B, C = propcalc.get_formulas("(a&b)->~c", "c", "~(a&b) ")
>>> A
(a&b)->~c
>>> B
c
>>> C
~(a&b)
```

We can also convert parse trees into formulas.

```
sage: t = ['a']
sage: u = ['~', ['|', ['&', 'a', 'b'], ['~', 'c']]]
sage: v = "b->(~c<->d) "
sage: formulas= propcalc.get_formulas(t, u, v)
sage: formulas[0]
a
sage: formulas[1]
~((a&b)|~c)
sage: formulas[2]
b->(~c<->d)
```

```
>>> from sage.all import *
>>> t = ['a']
>>> u = ['~', ['|', ['&', 'a', 'b'], ['~', 'c']]]
>>> v = "b->(~c<->d) "
```

(continues on next page)

(continued from previous page)

```
>>> formulas= propcalc.get_formulas(t, u, v)
>>> formulas[Integer(0)]
a
>>> formulas[Integer(1)]
~ ( (a&b) | ~c)
>>> formulas[Integer(2)]
b-> (~c<->d)
```

AUTHORS:

- Paul Scurek (2013-08-12)

BOOLEAN FORMULAS

Formulas consist of the operators `&`, `|`, `~`, `^`, `->`, `<->`, corresponding to and, or, not, xor, if...then, if and only if. Operators can be applied to variables that consist of a leading letter and trailing underscores and alphanumerics. Parentheses may be used to explicitly show order of operation.

EXAMPLES:

Create boolean formulas and combine them with `ifthen()` method:

```
sage: import sage.logic.propcalc as propcalc
sage: f = propcalc.formula("a & ( (b|c) ^ a->c) <-> b")
sage: g = propcalc.formula("boolean<->algebra")
sage: (f&~g).ifthen(f)
((a & ( (b|c) ^ a->c) <-> b) & (~ (boolean<->algebra))) -> (a & ( (b|c) ^ a->c) <-> b)
```

```
>>> from sage.all import *
>>> import sage.logic.propcalc as propcalc
>>> f = propcalc.formula("a & ( (b|c) ^ a->c) <-> b")
>>> g = propcalc.formula("boolean<->algebra")
>>> (f&~g).ifthen(f)
((a & ( (b|c) ^ a->c) <-> b) & (~ (boolean<->algebra))) -> (a & ( (b|c) ^ a->c) <-> b)
```

We can create a truth table from a formula:

```
sage: f.truthtable()
a      b      c      value
False  False  False  True
False  False  True   True
False  True   False  False
False  True   True   False
True   False  False  True
True   False  True   False
True   True   False  True
True   True   True   True
sage: f.truthtable(end=3)
a      b      c      value
False  False  False  True
False  False  True   True
False  True   False  False
sage: f.truthtable(start=4)
a      b      c      value
True   False  False  True
```

(continues on next page)

(continued from previous page)

```

True   False  True   False
True   True   False  True
True   True   True   True
sage: propcalc.formula("a").truthtable()
a      value
False  False
True   True

```

```

>>> from sage.all import *
>>> f.truthtable()
a      b      c      value
False  False  False  True
False  False  True   True
False  True   False  False
False  True   True   False
True   False  False  True
True   False  True   False
True   True   False  True
True   True   True   True
>>> f.truthtable(end=Integer(3))
a      b      c      value
False  False  False  True
False  False  True   True
False  True   False  False
>>> f.truthtable(start=Integer(4))
a      b      c      value
True   False  False  True
True   False  True   False
True   True   False  True
True   True   True   True
>>> propcalc.formula("a").truthtable()
a      value
False  False
True   True

```

Now we can evaluate the formula for a given set of inputs:

```

sage: f.evaluate({'a':True, 'b':False, 'c':True})
False
sage: f.evaluate({'a':False, 'b':False, 'c':True})
True

```

```

>>> from sage.all import *
>>> f.evaluate({'a':True, 'b':False, 'c':True})
False
>>> f.evaluate({'a':False, 'b':False, 'c':True})
True

```

And we can convert a boolean formula to conjunctive normal form:

```

sage: f.convert_cnf_table()
sage: f

```

(continues on next page)

(continued from previous page)

```
(a|~b|c)&(a|~b|~c)&(~a|b|~c)
sage: f.convert_cnf_recur()
sage: f
(a|~b|c)&(a|~b|~c)&(~a|b|~c)
```

```
>>> from sage.all import *
>>> f.convert_cnf_table()
>>> f
(a|~b|c)&(a|~b|~c)&(~a|b|~c)
>>> f.convert_cnf_recur()
>>> f
(a|~b|c)&(a|~b|~c)&(~a|b|~c)
```

Or determine if an expression is satisfiable, a contradiction, or a tautology:

```
sage: f = propcalc.formula("a|b")
sage: f.is_satisfiable()
True
sage: f = f & ~f
sage: f.is_satisfiable()
False
sage: f.is_contradiction()
True
sage: f = f | ~f
sage: f.is_tautology()
True
```

```
>>> from sage.all import *
>>> f = propcalc.formula("a|b")
>>> f.is_satisfiable()
True
>>> f = f & ~f
>>> f.is_satisfiable()
False
>>> f.is_contradiction()
True
>>> f = f | ~f
>>> f.is_tautology()
True
```

The equality operator compares semantic equivalence:

```
sage: f = propcalc.formula("(a|b)&c")
sage: g = propcalc.formula("c&(b|a)")
sage: f == g
True
sage: g = propcalc.formula("a|b&c")
sage: f == g
False
```

```
>>> from sage.all import *
>>> f = propcalc.formula("(a|b)&c")
```

(continues on next page)

(continued from previous page)

```
>>> g = propcalc.formula("c&(b|a)")
>>> f == g
True
>>> g = propcalc.formula("a|b&c")
>>> f == g
False
```

It is an error to create a formula with bad syntax:

```
sage: propcalc.formula("")
Traceback (most recent call last):
...
SyntaxError: malformed statement
sage: propcalc.formula("a&b~(c|(d)")
Traceback (most recent call last):
...
SyntaxError: malformed statement
sage: propcalc.formula("a&&b")
Traceback (most recent call last):
...
SyntaxError: malformed statement
sage: propcalc.formula("a&b a")
Traceback (most recent call last):
...
SyntaxError: malformed statement
```

```
>>> from sage.all import *
>>> propcalc.formula("")
Traceback (most recent call last):
...
SyntaxError: malformed statement
>>> propcalc.formula("a&b~(c|(d)")
Traceback (most recent call last):
...
SyntaxError: malformed statement
>>> propcalc.formula("a&&b")
Traceback (most recent call last):
...
SyntaxError: malformed statement
>>> propcalc.formula("a&b a")
Traceback (most recent call last):
...
SyntaxError: malformed statement
```

It is also an error to not abide by the naming conventions:

```
sage: propcalc.formula("~a&9b")
Traceback (most recent call last):
...
NameError: invalid variable name 9b: identifiers must begin with a letter and contain
↳ only alphanumerics and underscores
```

```
>>> from sage.all import *
>>> propcalc.formula("~a&9b")
Traceback (most recent call last):
...
NameError: invalid variable name 9b: identifiers must begin with a letter and contain
↳ only alphanumerics and underscores
```

AUTHORS:

- Chris Gorecki (2006): initial version
- Paul Scurek (2013-08-03): added `polish_notation`, `full_tree`, updated docstring formatting
- Paul Scurek (2013-08-08): added `implies()`

```
class sage.logic.boolformula.BooleanFormula(exp, tree, vo)
```

Bases: object

Boolean formulas.

INPUT:

- `self` – calling object
- `exp` – string; this contains the boolean expression to be manipulated
- `tree` – list; this contains the parse tree of the expression
- `vo` – list; this contains the variables in the expression, in the order that they appear; each variable only occurs once in the list

```
add_statement(other, op)
```

Combine two formulas with the given operator.

INPUT:

- `other` – instance of `BooleanFormula`; this is the formula on the right of the operator
- `op` – string; this is the operator used to combine the two formulas

OUTPUT: the result as an instance of `BooleanFormula`

EXAMPLES:

This example shows how to create a new formula from two others:

```
sage: import sage.logic.propcalc as propcalc
sage: s = propcalc.formula("a&b")
sage: f = propcalc.formula("c^d")
sage: s.add_statement(f, '|')
(a&b) | (c^d)

sage: s.add_statement(f, '->')
(a&b) -> (c^d)
```

```
>>> from sage.all import *
>>> import sage.logic.propcalc as propcalc
>>> s = propcalc.formula("a&b")
>>> f = propcalc.formula("c^d")
>>> s.add_statement(f, '|')
```

(continues on next page)

(continued from previous page)

```
(a&b) | (c^d)

>>> s.add_statement(f, '->')
(a&b) -> (c^d)
```

convert_cnf()

Convert boolean formula to conjunctive normal form.

OUTPUT: an instance of *BooleanFormula* in conjunctive normal form

EXAMPLES:

This example illustrates how to convert a formula to cnf:

```
sage: import sage.logic.propcalc as propcalc
sage: s = propcalc.formula("a ^ b <-> c")
sage: s.convert_cnf()
sage: s
(a|b|~c) & (a|~b|c) & (~a|b|c) & (~a|~b|~c)
```

```
>>> from sage.all import *
>>> import sage.logic.propcalc as propcalc
>>> s = propcalc.formula("a ^ b <-> c")
>>> s.convert_cnf()
>>> s
(a|b|~c) & (a|~b|c) & (~a|b|c) & (~a|~b|~c)
```

We now show that *convert_cnf()* and *convert_cnf_table()* are aliases:

```
sage: t = propcalc.formula("a ^ b <-> c")
sage: t.convert_cnf_table(); t
(a|b|~c) & (a|~b|c) & (~a|b|c) & (~a|~b|~c)
sage: t == s
True
```

```
>>> from sage.all import *
>>> t = propcalc.formula("a ^ b <-> c")
>>> t.convert_cnf_table(); t
(a|b|~c) & (a|~b|c) & (~a|b|c) & (~a|~b|~c)
>>> t == s
True
```

Note

This method creates the cnf parse tree by examining the logic table of the formula. Creating the table requires $O(2^n)$ time where n is the number of variables in the formula.

convert_cnf_recur()

Convert boolean formula to conjunctive normal form.

OUTPUT: an instance of *BooleanFormula* in conjunctive normal form

EXAMPLES:

This example shows how to convert a formula to conjunctive normal form:

```
sage: import sage.logic.propcalc as propcalc
sage: s = propcalc.formula("a^b<->c")
sage: s.convert_cnf_recur()
sage: s
(~a|a|c)&(~b|a|c)&(~a|b|c)&(~b|b|c)&(~c|a|b)&(~c|~a|~b)
```

```
>>> from sage.all import *
>>> import sage.logic.propcalc as propcalc
>>> s = propcalc.formula("a^b<->c")
>>> s.convert_cnf_recur()
>>> s
(~a|a|c)&(~b|a|c)&(~a|b|c)&(~b|b|c)&(~c|a|b)&(~c|~a|~b)
```

Note

This function works by applying a set of rules that are guaranteed to convert the formula. Worst case the converted expression has an $O(2^n)$ increase in size (and time as well), but if the formula is already in CNF (or close to) it is only $O(n)$.

This function can require an exponential blow up in space from the original expression. This in turn can require large amounts of time. Unless a formula is already in (or close to) being in cnf `convert_cnf()` is typically preferred, but results can vary.

`convert_cnf_table()`

Convert boolean formula to conjunctive normal form.

OUTPUT: an instance of *BooleanFormula* in conjunctive normal form

EXAMPLES:

This example illustrates how to convert a formula to cnf:

```
sage: import sage.logic.propcalc as propcalc
sage: s = propcalc.formula("a ^ b <-> c")
sage: s.convert_cnf()
sage: s
(a|b|~c)&(a|~b|c)&(~a|b|c)&(~a|~b|~c)
```

```
>>> from sage.all import *
>>> import sage.logic.propcalc as propcalc
>>> s = propcalc.formula("a ^ b <-> c")
>>> s.convert_cnf()
>>> s
(a|b|~c)&(a|~b|c)&(~a|b|c)&(~a|~b|~c)
```

We now show that `convert_cnf()` and `convert_cnf_table()` are aliases:

```
sage: t = propcalc.formula("a ^ b <-> c")
sage: t.convert_cnf_table(); t
(a|b|~c)&(a|~b|c)&(~a|b|c)&(~a|~b|~c)
sage: t == s
True
```

```
>>> from sage.all import *
>>> t = propcalc.formula("a ^ b <-> c")
>>> t.convert_cnf_table(); t
(a|b|~c) & (a|~b|c) & (~a|b|c) & (~a|~b|~c)
>>> t == s
True
```

Note

This method creates the cnf parse tree by examining the logic table of the formula. Creating the table requires $O(2^n)$ time where n is the number of variables in the formula.

convert_expression()

Convert the string representation of a formula to conjunctive normal form.

EXAMPLES:

```
sage: import sage.logic.propcalc as propcalc
sage: s = propcalc.formula("a^b<->c")
sage: s.convert_expression(); s
a^b<->c
```

```
>>> from sage.all import *
>>> import sage.logic.propcalc as propcalc
>>> s = propcalc.formula("a^b<->c")
>>> s.convert_expression(); s
a^b<->c
```

convert_opt (tree)

Convert a parse tree to the tuple form used by `bool_opt()`.

INPUT:

- `tree` – list; this is a branch of a parse tree and can only contain the ‘&’, ‘|’ and ‘~’ operators along with variables

OUTPUT: a 3-tuple

EXAMPLES:

This example illustrates the conversion of a formula into its corresponding tuple:

```
sage: import sage.logic.propcalc as propcalc, sage.logic.logicparser as_
↪logicparser
sage: s = propcalc.formula("a&(b|~c)")
sage: tree = ['&', 'a', ['|', 'b', ['~', 'c', None]]]
sage: logicparser.apply_func(tree, s.convert_opt)
('and', ('prop', 'a'), ('or', ('prop', 'b'), ('not', ('prop', 'c'))))
```

```
>>> from sage.all import *
>>> import sage.logic.propcalc as propcalc, sage.logic.logicparser as_
↪logicparser
>>> s = propcalc.formula("a&(b|~c)")
```

(continues on next page)

(continued from previous page)

```
>>> tree = ['&', 'a', ['|', 'b', ['~', 'c', None]]]
>>> logicparser.apply_func(tree, s.convert_opt)
('and', ('prop', 'a'), ('or', ('prop', 'b'), ('not', ('prop', 'c'))))
```

Note

This function only works on one branch of the parse tree. To apply the function to every branch of a parse tree, pass the function as an argument in `apply_func()` in `logicparser`.

dist_not (*tree*)

Distribute '~' operators over '&' and '|' operators.

INPUT:

- *tree* a list; this represents a branch of a parse tree

OUTPUT: a new list

EXAMPLES:

This example illustrates the distribution of '~' over '&':

```
sage: import sage.logic.propcalc as propcalc, sage.logic.logicparser as _
      ↪ logicparser
sage: s = propcalc.formula("~(a&b)")
sage: tree = ['~', ['&', 'a', 'b'], None]
sage: logicparser.apply_func(tree, s.dist_not) #long time
['|', ['~', 'a', None], ['~', 'b', None]]
```

```
>>> from sage.all import *
>>> import sage.logic.propcalc as propcalc, sage.logic.logicparser as _
      ↪ logicparser
>>> s = propcalc.formula("~(a&b)")
>>> tree = ['~', ['&', 'a', 'b'], None]
>>> logicparser.apply_func(tree, s.dist_not) #long time
['|', ['~', 'a', None], ['~', 'b', None]]
```

Note

This function only operates on a single branch of a parse tree. To apply the function to an entire parse tree, pass the function as an argument to `apply_func()` in `logicparser`.

dist_ors (*tree*)

Distribute '|' over '&'.
INPUT:

- *tree* – list; this represents a branch of a parse tree

OUTPUT: a new list

EXAMPLES:

This example illustrates the distribution of '|' over '&':

```
sage: import sage.logic.propcalc as propcalc, sage.logic.logicparser as _
↳logicparser
sage: s = propcalc.formula("(a&b)|(a&c)")
sage: tree = ['|', ['&', 'a', 'b'], ['&', 'a', 'c']]
sage: logicparser.apply_func(tree, s.dist_ors) #long time
['&', ['&', ['|', 'a', 'a'], ['|', 'b', 'a']], ['&', ['|', 'a', 'c'], ['|', 'b
↳', 'c']]]
```

```
>>> from sage.all import *
>>> import sage.logic.propcalc as propcalc, sage.logic.logicparser as _
↳logicparser
>>> s = propcalc.formula("(a&b)|(a&c)")
>>> tree = ['|', ['&', 'a', 'b'], ['&', 'a', 'c']]
>>> logicparser.apply_func(tree, s.dist_ors) #long time
['&', ['&', ['|', 'a', 'a'], ['|', 'b', 'a']], ['&', ['|', 'a', 'c'], ['|', 'b
↳', 'c']]]
```

Note

This function only operates on a single branch of a parse tree. To apply the function to an entire parse tree, pass the function as an argument to `apply_func()` in `logicparser`.

equivalent (*other*)

Determine if two formulas are semantically equivalent.

INPUT:

- `self` – calling object
- `other` – instance of `BooleanFormula` class

OUTPUT: a boolean value to be determined as follows:

True – if the two formulas are logically equivalent

False – if the two formulas are not logically equivalent

EXAMPLES:

This example shows how to check for logical equivalence:

```
sage: import sage.logic.propcalc as propcalc
sage: f = propcalc.formula("(a|b)&c")
sage: g = propcalc.formula("c&(a|b)")
sage: f.equivalent(g)
True

sage: g = propcalc.formula("a|b&c")
sage: f.equivalent(g)
False
```

```
>>> from sage.all import *
>>> import sage.logic.propcalc as propcalc
>>> f = propcalc.formula("(a|b)&c")
```

(continues on next page)

(continued from previous page)

```
>>> g = propcalc.formula("c&(a|b)")
>>> f.equivalent(g)
True

>>> g = propcalc.formula("a|b&c")
>>> f.equivalent(g)
False
```

evaluate(var_values)

Evaluate a formula for the given input values.

INPUT:

- var_values – dictionary; this contains the pairs of variables and their boolean values

OUTPUT: the result of the evaluation as a boolean

EXAMPLES:

This example illustrates the evaluation of a boolean formula:

```
sage: import sage.logic.propcalc as propcalc
sage: f = propcalc.formula("a&b|c")
sage: f.evaluate({'a':False, 'b':False, 'c':True})
True
sage: f.evaluate({'a':True, 'b':False, 'c':False})
False
```

```
>>> from sage.all import *
>>> import sage.logic.propcalc as propcalc
>>> f = propcalc.formula("a&b|c")
>>> f.evaluate({'a':False, 'b':False, 'c':True})
True
>>> f.evaluate({'a':True, 'b':False, 'c':False})
False
```

full_tree()

Return a full syntax parse tree of the calling formula.

OUTPUT: the full syntax parse tree as a nested list

EXAMPLES:

This example shows how to find the full syntax parse tree of a formula:

```
sage: import sage.logic.propcalc as propcalc
sage: s = propcalc.formula("a->(b&c)")
sage: s.full_tree()
['->', 'a', ['&', 'b', 'c']]

sage: t = propcalc.formula("a & ((~b | c) ^ a -> c) <-> ~b")
sage: t.full_tree()
['<->', ['&', 'a', ['->', ['^', ['|', ['~', 'b'], 'c'], 'a'], 'c']], ['~', 'b', '<->']]

sage: f = propcalc.formula("~(a&b)")
```

(continues on next page)

(continued from previous page)

```
sage: f.full_tree()
['~', ['~', ['&', 'a', ['~', 'b']]]]
```

```
>>> from sage.all import *
>>> import sage.logic.propcalc as propcalc
>>> s = propcalc.formula("a->(b&c) ")
>>> s.full_tree()
['->', 'a', ['&', 'b', 'c']]

>>> t = propcalc.formula("a & ((~b | c) ^ a -> c) <-> ~b")
>>> t.full_tree()
['<->', ['&', 'a', ['->', ['^', ['|', ['~', 'b'], 'c'], 'a'], 'c']], ['~', 'b',
↪']]

>>> f = propcalc.formula("~~(a&~b) ")
>>> f.full_tree()
['~', ['~', ['&', 'a', ['~', 'b']]]]
```

Note

This function is used by other functions in the logic module that perform syntactic operations on a boolean formula.

AUTHORS:

- Paul Scurek (2013-08-03)

get_bit (*x*, *c*)

Determine if bit *c* of the number *x* is 1.

INPUT:

- *x* – integer; this is the number from which to take the bit
- *c* – integer; this is the bit number to be taken, where 0 is the low order bit

OUTPUT: a boolean to be determined as follows:

- True if bit *c* of *x* is 1.
- False if bit *c* of *x* is not 1.

EXAMPLES:

This example illustrates the use of `get_bit()`:

```
sage: import sage.logic.propcalc as propcalc
sage: s = propcalc.formula("a&b")
sage: s.get_bit(2, 1)
True
sage: s.get_bit(8, 0)
False
```

```
>>> from sage.all import *
>>> import sage.logic.propcalc as propcalc
```

(continues on next page)

(continued from previous page)

```
>>> s = propcalc.formula("a&b")
>>> s.get_bit(Integer(2), Integer(1))
True
>>> s.get_bit(Integer(8), Integer(0))
False
```

It is not an error to have a bit out of range:

```
sage: s.get_bit(64, 7)
False
```

```
>>> from sage.all import *
>>> s.get_bit(Integer(64), Integer(7))
False
```

Nor is it an error to use a negative number:

```
sage: s.get_bit(-1, 3)
False
sage: s.get_bit(64, -1)
True
sage: s.get_bit(64, -2)
False
```

```
>>> from sage.all import *
>>> s.get_bit(-Integer(1), Integer(3))
False
>>> s.get_bit(Integer(64), -Integer(1))
True
>>> s.get_bit(Integer(64), -Integer(2))
False
```

Note

The 0 bit is the low order bit. Errors should be handled gracefully by a return of `False`, and negative numbers `x` always return `False` while a negative `c` will index from the high order bit.

`get_next_op(str)`

Return the next operator in a string.

INPUT:

- `str` – string; this contains a logical expression

OUTPUT: the next operator as a string

EXAMPLES:

This example illustrates how to find the next operator in a formula:

```
sage: import sage.logic.propcalc as propcalc
sage: s = propcalc.formula("f&p")
```

(continues on next page)

(continued from previous page)

```
sage: s.get_next_op("abra|cadabra")
'|'
```

```
>>> from sage.all import *
>>> import sage.logic.propcalc as propcalc
>>> s = propcalc.formula("f&p")
>>> s.get_next_op("abra|cadabra")
'|'
```

Note

The parameter `str` is not necessarily the string representation of the calling object.

`iff`(*other*)

Combine two formulas with the $\leftrightarrow$ operator.

INPUT:

- `other` – boolean formula; this is the formula on the right side of the operator

OUTPUT:

A boolean formula of the form `self  $\leftrightarrow$  other`.

EXAMPLES:

This example illustrates how to combine two formulas with ' $\leftrightarrow$ ':

```
sage: import sage.logic.propcalc as propcalc
sage: s = propcalc.formula("a&b")
sage: f = propcalc.formula("c^d")
sage: s.iff(f)
(a&b) ↔ (c^d)
```

```
>>> from sage.all import *
>>> import sage.logic.propcalc as propcalc
>>> s = propcalc.formula("a&b")
>>> f = propcalc.formula("c^d")
>>> s.iff(f)
(a&b) ↔ (c^d)
```

`ifthen`(*other*)

Combine two formulas with the $\rightarrow$ operator.

INPUT:

- `other` – boolean formula; this is the formula on the right side of the operator

OUTPUT:

A boolean formula of the form `self  $\rightarrow$  other`.

EXAMPLES:

This example illustrates how to combine two formulas with ' $\rightarrow$ ':

```
sage: import sage.logic.propcalc as propcalc
sage: s = propcalc.formula("a&b")
sage: f = propcalc.formula("c^d")
sage: s.ifthen(f)
(a&b)->(c^d)
```

```
>>> from sage.all import *
>>> import sage.logic.propcalc as propcalc
>>> s = propcalc.formula("a&b")
>>> f = propcalc.formula("c^d")
>>> s.ifthen(f)
(a&b)->(c^d)
```

implies (*other*)

Determine if calling formula implies other formula.

INPUT:

- self – calling object
- other – instance of *BooleanFormula*

OUTPUT: a boolean value to be determined as follows:

- True – if self implies other
- False – if self does not imply ``other

EXAMPLES:

This example illustrates determining if one formula implies another:

```
sage: import sage.logic.propcalc as propcalc
sage: f = propcalc.formula("a<->b")
sage: g = propcalc.formula("b->a")
sage: f.implies(g)
True
```

```
>>> from sage.all import *
>>> import sage.logic.propcalc as propcalc
>>> f = propcalc.formula("a<->b")
>>> g = propcalc.formula("b->a")
>>> f.implies(g)
True
```

```
sage: h = propcalc.formula("a->(a|~b) ")
sage: i = propcalc.formula("a")
sage: h.implies(i)
False
```

```
>>> from sage.all import *
>>> h = propcalc.formula("a->(a|~b) ")
>>> i = propcalc.formula("a")
>>> h.implies(i)
False
```

AUTHORS:

- Paul Scurek (2013-08-08)

is_consequence (*hypotheses)

Determine if `self` (the desired conclusion) is a logical consequence of the hypotheses. The function call `is_consequence(conclusion, *hypotheses)` is a synonym for `conclusion.is_consequence(*hypotheses)`.

INPUT:

- *hypotheses – instances of *BooleanFormula*

OUTPUT: a boolean value to be determined as follows:

- True – if `self` (the desired conclusion) is a logical consequence of the set of hypotheses
- False – if `self` (the desired conclusion) is not a logical consequence of the set of hypotheses

EXAMPLES:

```
sage: from sage.logic.propcalc import formula
sage: formula("a | b").is_consequence(formula("b"))
True
sage: formula("a & b").is_consequence(formula("b"))
False
sage: formula("b").is_consequence(formula("a"), formula("a -> b"))
True
sage: formula("b -> a").is_consequence(formula("a -> b"))
False
sage: formula("~b -> ~a").is_consequence(formula("a -> b"))
True
```

```
>>> from sage.all import *
>>> from sage.logic.propcalc import formula
>>> formula("a | b").is_consequence(formula("b"))
True
>>> formula("a & b").is_consequence(formula("b"))
False
>>> formula("b").is_consequence(formula("a"), formula("a -> b"))
True
>>> formula("b -> a").is_consequence(formula("a -> b"))
False
>>> formula("~b -> ~a").is_consequence(formula("a -> b"))
True
```

```
sage: f, g, h = propcalc.get_formulas("a & ~b", "c -> b", "c | e")
sage: propcalc.formula("a & e").is_consequence(f, g, h)
True
sage: i = propcalc.formula("a & ~e")
sage: i.is_consequence(f, g, h)
False
sage: from sage.logic.boolformula import is_consequence
sage: is_consequence(i, f, g, h)
False
sage: is_consequence(propcalc.formula("(p <-> q) & r) -> ~c"), f, g, h)
True
```

```

>>> from sage.all import *
>>> f, g, h = propcalc.get_formulas("a & ~b", "c -> b", "c | e")
>>> propcalc.formula("a & e").is_consequence(f, g, h)
True
>>> i = propcalc.formula("a & ~e")
>>> i.is_consequence(f, g, h)
False
>>> from sage.logic.boolformula import is_consequence
>>> is_consequence(i, f, g, h)
False
>>> is_consequence(propcalc.formula("(p <-> q) & r) -> ~c"), f, g, h)
True

```

Only a tautology is a logical consequence of an empty set of formulas:

```

sage: propcalc.formula("a | ~a").is_consequence()
True
sage: propcalc.formula("a | b").is_consequence()
False

```

```

>>> from sage.all import *
>>> propcalc.formula("a | ~a").is_consequence()
True
>>> propcalc.formula("a | b").is_consequence()
False

```

AUTHORS:

- Paul Scurek (2013-08-12)

is_contradiction()

Determine if the formula is always `False`.

OUTPUT: a boolean value to be determined as follows:

- `True` if the formula is a contradiction.
- `False` if the formula is not a contradiction.

EXAMPLES:

This example illustrates how to check if a formula is a contradiction.

```

sage: import sage.logic.propcalc as propcalc
sage: f = propcalc.formula("a&~a")
sage: f.is_contradiction()
True

sage: f = propcalc.formula("a|~a")
sage: f.is_contradiction()
False

sage: f = propcalc.formula("a|b")
sage: f.is_contradiction()
False

```

```
>>> from sage.all import *
>>> import sage.logic.propcalc as propcalc
>>> f = propcalc.formula("a&~a")
>>> f.is_contradiction()
True

>>> f = propcalc.formula("a|~a")
>>> f.is_contradiction()
False

>>> f = propcalc.formula("a|b")
>>> f.is_contradiction()
False
```

is_satisfiable()

Determine if the formula is True for some assignment of values.

OUTPUT: a boolean value to be determined as follows:

- True if there is an assignment of values that makes the formula True.
- False if the formula cannot be made True by any assignment of values.

EXAMPLES:

This example illustrates how to check a formula for satisfiability:

```
sage: import sage.logic.propcalc as propcalc
sage: f = propcalc.formula("a|b")
sage: f.is_satisfiable()
True

sage: g = f & (~f)
sage: g.is_satisfiable()
False
```

```
>>> from sage.all import *
>>> import sage.logic.propcalc as propcalc
>>> f = propcalc.formula("a|b")
>>> f.is_satisfiable()
True

>>> g = f & (~f)
>>> g.is_satisfiable()
False
```

is_tautology()

Determine if the formula is always True.

OUTPUT: a boolean value to be determined as follows:

- True if the formula is a tautology.
- False if the formula is not a tautology.

EXAMPLES:

This example illustrates how to check if a formula is a tautology:

```

sage: import sage.logic.propcalc as propcalc
sage: f = propcalc.formula("a|~a")
sage: f.is_tautology()
True

sage: f = propcalc.formula("a&~a")
sage: f.is_tautology()
False

sage: f = propcalc.formula("a&b")
sage: f.is_tautology()
False

```

```

>>> from sage.all import *
>>> import sage.logic.propcalc as propcalc
>>> f = propcalc.formula("a|~a")
>>> f.is_tautology()
True

>>> f = propcalc.formula("a&~a")
>>> f.is_tautology()
False

>>> f = propcalc.formula("a&b")
>>> f.is_tautology()
False

```

length()

Return the length of `self`.

OUTPUT:

The length of the Boolean formula. This is the number of operators plus the number of variables (counting multiplicity). Parentheses are ignored.

EXAMPLES:

```

sage: import sage.logic.propcalc as propcalc
sage: s = propcalc.formula("a")
sage: s.length()
1
sage: s = propcalc.formula("(a)")
sage: s.length()
1
sage: s = propcalc.formula("~a")
sage: s.length()
2
sage: s = propcalc.formula("a -> b")
sage: s.length()
3
sage: s = propcalc.formula("alpha -> beta")
sage: s.length()
3
sage: s = propcalc.formula("a -> a")

```

(continues on next page)

(continued from previous page)

```

sage: s.length()
3
sage: s = propcalc.formula("~(a -> b) ")
sage: s.length()
4
sage: s = propcalc.formula("((a&b) | (a&c)) -> ~d")
sage: s.length()
10

```

```

>>> from sage.all import *
>>> import sage.logic.propcalc as propcalc
>>> s = propcalc.formula("a")
>>> s.length()
1
>>> s = propcalc.formula("(a) ")
>>> s.length()
1
>>> s = propcalc.formula("~a")
>>> s.length()
2
>>> s = propcalc.formula("a -> b")
>>> s.length()
3
>>> s = propcalc.formula("alpha -> beta")
>>> s.length()
3
>>> s = propcalc.formula("a -> a")
>>> s.length()
3
>>> s = propcalc.formula("~(a -> b) ")
>>> s.length()
4
>>> s = propcalc.formula("((a&b) | (a&c)) -> ~d")
>>> s.length()
10

```

polish_notation()

Convert the calling boolean formula into polish notation.

OUTPUT: string representation of the formula in polish notation

EXAMPLES:

This example illustrates converting a formula to polish notation:

```

sage: import sage.logic.propcalc as propcalc
sage: f = propcalc.formula("~~a | (c->b) ")
sage: f.polish_notation()
'| ~~a->cb'

sage: g = propcalc.formula("(a | ~b) -> c")
sage: g.polish_notation()
'-> | a~bc'

```

```
>>> from sage.all import *
>>> import sage.logic.propcalc as propcalc
>>> f = propcalc.formula("~a | (c->b) ")
>>> f.polish_notation()
'|~a->cb'

>>> g = propcalc.formula("(a|~b)->c")
>>> g.polish_notation()
'->|a~bc'
```

AUTHORS:

- Paul Scurek (2013-08-03)

reduce_op (tree)

Convert if-and-only-if, if-then, and xor operations to operations only involving and/or operations.

INPUT:

- tree – list; this represents a branch of a parse tree

OUTPUT:

A new list with no '^', '->', or '<->' as first element of list.

EXAMPLES:

This example illustrates the use of `reduce_op()` with `apply_func()`:

```
sage: import sage.logic.propcalc as propcalc, sage.logic.logicparser as _
      ↪logicparser
sage: s = propcalc.formula("a->b^c")
sage: tree = ['->', 'a', ['^', 'b', 'c']]
sage: logicparser.apply_func(tree, s.reduce_op)
['|', ['~', 'a', None], ['&', ['|', 'b', 'c'], ['~', ['&', 'b', 'c'], None]]]
```

```
>>> from sage.all import *
>>> import sage.logic.propcalc as propcalc, sage.logic.logicparser as _
      ↪logicparser
>>> s = propcalc.formula("a->b^c")
>>> tree = ['->', 'a', ['^', 'b', 'c']]
>>> logicparser.apply_func(tree, s.reduce_op)
['|', ['~', 'a', None], ['&', ['|', 'b', 'c'], ['~', ['&', 'b', 'c'], None]]]
```

Note

This function only operates on a single branch of a parse tree. To apply the function to an entire parse tree, pass the function as an argument to `apply_func()` in `logicparser`.

satformat ()

Return the satformat representation of a boolean formula.

OUTPUT: the satformat of the formula as a string

EXAMPLES:

This example illustrates how to find the satformat of a formula:

```
sage: import sage.logic.propcalc as propcalc
sage: f = propcalc.formula("a & ((b | c) ^ a -> c) <-> b")
sage: f.convert_cnf()
sage: f
(a | ~b | c) & (a | ~b | ~c) & (~a | b | ~c)
sage: f.satformat()
'p cnf 3 0\n1 -2 3 0 1 -2 -3 \n0 -1 2 -3'
```

```
>>> from sage.all import *
>>> import sage.logic.propcalc as propcalc
>>> f = propcalc.formula("a & ((b | c) ^ a -> c) <-> b")
>>> f.convert_cnf()
>>> f
(a | ~b | c) & (a | ~b | ~c) & (~a | b | ~c)
>>> f.satformat()
'p cnf 3 0\n1 -2 3 0 1 -2 -3 \n0 -1 2 -3'
```

Note

See www.cs.ubc.ca/~hoos/SATLIB/Benchmarks/SAT/satformat.ps for a description of satformat.

If the instance of boolean formula has not been converted to CNF form by a call to `convert_cnf()` or `convert_cnf_recur()`, then `satformat()` will call `convert_cnf()`. Please see the notes for `convert_cnf()` and `convert_cnf_recur()` for performance issues.

to_infix(tree)

Convert a parse tree from prefix to infix form.

INPUT:

- `tree` – list; this represents a branch of a parse tree

OUTPUT: a new list

EXAMPLES:

This example shows how to convert a parse tree from prefix to infix form:

```
sage: import sage.logic.propcalc as propcalc, sage.logic.logicparser as _
↳ logicparser
sage: s = propcalc.formula("(a&b) | (a&c)")
sage: tree = ['|', ['&', 'a', 'b'], ['&', 'a', 'c']]
sage: logicparser.apply_func(tree, s.to_infix)
[['a', '&', 'b'], '|', ['a', '&', 'c']]
```

```
>>> from sage.all import *
>>> import sage.logic.propcalc as propcalc, sage.logic.logicparser as _
↳ logicparser
>>> s = propcalc.formula("(a&b) | (a&c)")
>>> tree = ['|', ['&', 'a', 'b'], ['&', 'a', 'c']]
>>> logicparser.apply_func(tree, s.to_infix)
[['a', '&', 'b'], '|', ['a', '&', 'c']]
```

Note

This function only operates on a single branch of a parse tree. To apply the function to an entire parse tree, pass the function as an argument to `apply_func()` in `logicparser`.

tree()

Return the parse tree of this boolean expression.

OUTPUT: the parse tree as a nested list

EXAMPLES:

This example illustrates how to find the parse tree of a boolean formula:

```
sage: import sage.logic.propcalc as propcalc
sage: s = propcalc.formula("man -> monkey & human")
sage: s.tree()
['->', 'man', ['&', 'monkey', 'human']]
```

```
>>> from sage.all import *
>>> import sage.logic.propcalc as propcalc
>>> s = propcalc.formula("man -> monkey & human")
>>> s.tree()
['->', 'man', ['&', 'monkey', 'human']]
```

```
sage: f = propcalc.formula("a & ((~b | c) ^ a -> c) <-> ~b")
sage: f.tree()
['<->',
 ['&', 'a', ['->', ['^', ['|', ['~', 'b', None], 'c'], 'a'], 'c']],
 ['~', 'b', None]]
```

```
>>> from sage.all import *
>>> f = propcalc.formula("a & ((~b | c) ^ a -> c) <-> ~b")
>>> f.tree()
['<->',
 ['&', 'a', ['->', ['^', ['|', ['~', 'b', None], 'c'], 'a'], 'c']],
 ['~', 'b', None]]
```

Note

This function is used by other functions in the logic module that perform semantic operations on a boolean formula.

truthtable (start=0, end=-1)

Return a truth table for the calling formula.

INPUT:

- `start` – (default: 0) an integer; this is the first row of the truth table to be created
- `end` – (default: -1) an integer; this is the last row of the truth table to be created

OUTPUT: the truth table as a 2-D array

EXAMPLES:

This example illustrates the creation of a truth table:

```
sage: import sage.logic.propcalc as propcalc
sage: s = propcalc.formula("a&b|~(c|a)")
sage: s.truthtable()
a      b      c      value
False  False  False  True
False  False  True   False
False  True   False  True
False  True   True   False
True   False  False  False
True   False  True   False
True   True   False  True
True   True   True   True
```

```
>>> from sage.all import *
>>> import sage.logic.propcalc as propcalc
>>> s = propcalc.formula("a&b|~(c|a)")
>>> s.truthtable()
a      b      c      value
False  False  False  True
False  False  True   False
False  True   False  True
False  True   True   False
True   False  False  False
True   False  True   False
True   True   False  True
True   True   True   True
```

We can now create a truthtable of rows 1 to 4, inclusive:

```
sage: s.truthtable(1, 5)
a      b      c      value
False  False  True   False
False  True   False  True
False  True   True   False
True   False  False  False
```

```
>>> from sage.all import *
>>> s.truthtable(Integer(1), Integer(5))
a      b      c      value
False  False  True   False
False  True   False  True
False  True   True   False
True   False  False  False
```

Note

Each row of the table corresponds to a binary number, with each variable associated to a column of the number, and taking on a true value if that column has a value of 1. Please see the logictable module for details. The function returns a table that start inclusive and end exclusive so `truthtable(0, 2)` will include row 0, but not row 2.

When sent with no start or end parameters, this is an exponential time function requiring $O(2^n)$ time, where n is the number of variables in the expression.

`sage.logic.boolformula.is_consequence(self, *hypotheses)`

Determine if `self` (the desired conclusion) is a logical consequence of the hypotheses. The function call `is_consequence(conclusion, *hypotheses)` is a synonym for `conclusion.is_consequence(*hypotheses)`.

INPUT:

- `*hypotheses` – instances of *BooleanFormula*

OUTPUT: a boolean value to be determined as follows:

- True – if `self` (the desired conclusion) is a logical consequence of the set of hypotheses
- False – if `self` (the desired conclusion) is not a logical consequence of the set of hypotheses

EXAMPLES:

```
sage: from sage.logic.propcalc import formula
sage: formula("a | b").is_consequence(formula("b"))
True
sage: formula("a & b").is_consequence(formula("b"))
False
sage: formula("b").is_consequence(formula("a"), formula("a -> b"))
True
sage: formula("b -> a").is_consequence(formula("a -> b"))
False
sage: formula("~b -> ~a").is_consequence(formula("a -> b"))
True
```

```
>>> from sage.all import *
>>> from sage.logic.propcalc import formula
>>> formula("a | b").is_consequence(formula("b"))
True
>>> formula("a & b").is_consequence(formula("b"))
False
>>> formula("b").is_consequence(formula("a"), formula("a -> b"))
True
>>> formula("b -> a").is_consequence(formula("a -> b"))
False
>>> formula("~b -> ~a").is_consequence(formula("a -> b"))
True
```

```
sage: f, g, h = propcalc.get_formulas("a & ~b", "c -> b", "c | e")
sage: propcalc.formula("a & e").is_consequence(f, g, h)
True
sage: i = propcalc.formula("a & ~e")
sage: i.is_consequence(f, g, h)
False
sage: from sage.logic.boolformula import is_consequence
sage: is_consequence(i, f, g, h)
False
```

(continues on next page)

(continued from previous page)

```
sage: is_consequence(propcalc.formula("((p <-> q) & r) -> ~c"), f, g, h)
True
```

```
>>> from sage.all import *
>>> f, g, h = propcalc.get_formulas("a & ~b", "c -> b", "c | e")
>>> propcalc.formula("a & e").is_consequence(f, g, h)
True
>>> i = propcalc.formula("a & ~e")
>>> i.is_consequence(f, g, h)
False
>>> from sage.logic.boolformula import is_consequence
>>> is_consequence(i, f, g, h)
False
>>> is_consequence(propcalc.formula("((p <-> q) & r) -> ~c"), f, g, h)
True
```

Only a tautology is a logical consequence of an empty set of formulas:

```
sage: propcalc.formula("a | ~a").is_consequence()
True
sage: propcalc.formula("a | b").is_consequence()
False
```

```
>>> from sage.all import *
>>> propcalc.formula("a | ~a").is_consequence()
True
>>> propcalc.formula("a | b").is_consequence()
False
```

AUTHORS:

- Paul Scurek (2013-08-12)

EVALUATION OF BOOLEAN FORMULAS

AUTHORS:

- Chris Gorecki (2006): initial version
- Paul Scurek (2013-08-05): updated docstring formatting

EXAMPLES:

We can assign values to the variables and evaluate a formula:

```
sage: import sage.logic.booleval as booleval
sage: t = ['|', ['&', 'a', 'b'], ['&', 'a', 'c']]
sage: d = {'a' : True, 'b' : False, 'c' : True}
sage: booleval.eval_formula(t, d)
True
```

```
>>> from sage.all import *
>>> import sage.logic.booleval as booleval
>>> t = ['|', ['&', 'a', 'b'], ['&', 'a', 'c']]
>>> d = {'a' : True, 'b' : False, 'c' : True}
>>> booleval.eval_formula(t, d)
True
```

We can change our assignment of values by modifying the dictionary:

```
sage: d['a'] = False
sage: booleval.eval_formula(t, d)
False
```

```
>>> from sage.all import *
>>> d['a'] = False
>>> booleval.eval_formula(t, d)
False
```

`sage.logic.booleval.eval_f(tree)`

Evaluate the tree.

INPUT:

- `tree` – list of three elements corresponding to a branch of a parse tree

OUTPUT: the result of the evaluation as a boolean value

EXAMPLES:

This example illustrates how to evaluate a parse tree:

```
sage: import sage.logic.booleval as booleval
sage: booleval.eval_f(['&', True, False])
False

sage: booleval.eval_f(['^', True, True])
False

sage: booleval.eval_f(['|', False, True])
True
```

```
>>> from sage.all import *
>>> import sage.logic.booleval as booleval
>>> booleval.eval_f(['&', True, False])
False

>>> booleval.eval_f(['^', True, True])
False

>>> booleval.eval_f(['|', False, True])
True
```

`sage.logic.booleval.eval_formula(tree, vdict)`

Evaluate the tree and return a boolean value.

INPUT:

- `tree` – list of three elements corresponding to a branch of a parse tree
- `vdict` – dictionary containing variable keys and boolean values

OUTPUT: the result of the evaluation as a boolean value

EXAMPLES:

This example illustrates evaluating a boolean formula:

```
sage: import sage.logic.booleval as booleval
sage: t = ['|', ['&', 'a', 'b'], ['&', 'a', 'c']]
sage: d = {'a' : True, 'b' : False, 'c' : True}
sage: booleval.eval_formula(t, d)
True
```

```
>>> from sage.all import *
>>> import sage.logic.booleval as booleval
>>> t = ['|', ['&', 'a', 'b'], ['&', 'a', 'c']]
>>> d = {'a' : True, 'b' : False, 'c' : True}
>>> booleval.eval_formula(t, d)
True
```

```
sage: d['a'] = False
sage: booleval.eval_formula(t, d)
False
```

```
>>> from sage.all import *
>>> d['a'] = False
>>> booleval.eval_formula(t, d)
False
```

`sage.logic.booleval.eval_op(op, lv, rv)`

Evaluate `lv` and `rv` according to the operator `op`.

INPUT:

- `op` – string or character representing a boolean operator
- `lv` – boolean or variable
- `rv` – boolean or variable

OUTPUT: the evaluation of `lv op rv` as a boolean value

EXAMPLES:

We can evaluate an operator given the values on either side:

```
sage: import sage.logic.booleval as booleval
sage: booleval.eval_op('&', True, False)
False

sage: booleval.eval_op('^', True, True)
False

sage: booleval.eval_op('|', False, True)
True
```

```
>>> from sage.all import *
>>> import sage.logic.booleval as booleval
>>> booleval.eval_op('&', True, False)
False

>>> booleval.eval_op('^', True, True)
False

>>> booleval.eval_op('|', False, True)
True
```


MODULE THAT CREATES AND MODIFIES PARSE TREES OF WELL FORMED BOOLEAN FORMULAS.

A parse tree of a boolean formula is a nested list, where each branch is either a single variable, or a formula composed of either two variables and a binary operator or one variable and a unary operator. The function `parse` produces a parse tree that is simplified for the purposes of more efficient truth value evaluation. The function `polish_parse()` produces the full parse tree of a boolean formula which is used in functions related to proof and inference. That is, `parse()` is meant to be used with functions in the logic module that perform semantic operations on a boolean formula, and `polish_parse()` is to be used with functions that perform syntactic operations on a boolean formula.

AUTHORS:

- Chris Gorecki (2007): initial version
- Paul Scurek (2013-08-01): added `polish_parse`, cleaned up python code, updated docstring formatting
- Paul Scurek (2013-08-06): added `recover_formula()`, `recover_formula_internal()`, `prefix_to_infix()`, `to_infix_internal()`
- Paul Scurek (2013-08-08): added `get_trees`, error handling in `polish_parse`, `recover_formula_internal`, and `tree_parse`

EXAMPLES:

Find the parse tree and variables of a string representation of a boolean formula:

```
sage: import sage.logic.logicparser as logicparser
sage: s = 'a|b&c'
sage: t = logicparser.parse(s)
sage: t
(['|', 'a', ['&', 'b', 'c']], ['a', 'b', 'c'])
```

```
>>> from sage.all import *
>>> import sage.logic.logicparser as logicparser
>>> s = 'a|b&c'
>>> t = logicparser.parse(s)
>>> t
(['|', 'a', ['&', 'b', 'c']], ['a', 'b', 'c'])
```

Find the full syntax parse tree of a string representation of a boolean formula:

```
sage: import sage.logic.logicparser as logicparser
sage: s = '(a&b)->~~c'
sage: logicparser.polish_parse(s)
['->', ['&', 'a', 'b'], ['~', ['~', 'c']]]
```

```
>>> from sage.all import *
>>> import sage.logic.logicparser as logicparser
>>> s = '(a&b)->~~c'
>>> logicparser.polish_parse(s)
['->', ['&', 'a', 'b'], ['~', ['~', 'c']]]
```

Find the tokens and distinct variables of a boolean formula:

```
sage: import sage.logic.logicparser as logicparser
sage: s = '~(a|~b)<->(c->c)'
sage: logicparser.tokenize(s)
(['(', '~', '(', 'a', '|', '~', 'b', ')', '<->', '(', 'c', '->', 'c', ')', ')'], ['a',
↪ 'b', 'c'])
```

```
>>> from sage.all import *
>>> import sage.logic.logicparser as logicparser
>>> s = '~(a|~b)<->(c->c)'
>>> logicparser.tokenize(s)
(['(', '~', '(', 'a', '|', '~', 'b', ')', '<->', '(', 'c', '->', 'c', ')', ')'], ['a',
↪ 'b', 'c'])
```

Find the parse tree of a boolean formula from a list of the formula's tokens:

```
sage: import sage.logic.logicparser as logicparser
sage: t = ['(', 'a', '->', '~', 'c', ')']
sage: logicparser.tree_parse(t)
['->', 'a', ['~', 'c', None]]
sage: r = ['(', '~', '~', 'a', '|', 'b', ')']
sage: logicparser.tree_parse(r)
['|', 'a', 'b']
```

```
>>> from sage.all import *
>>> import sage.logic.logicparser as logicparser
>>> t = ['(', 'a', '->', '~', 'c', ')']
>>> logicparser.tree_parse(t)
['->', 'a', ['~', 'c', None]]
>>> r = ['(', '~', '~', 'a', '|', 'b', ')']
>>> logicparser.tree_parse(r)
['|', 'a', 'b']
```

Find the full syntax parse tree of a boolean formula from a list of tokens:

```
sage: import sage.logic.logicparser as logicparser
sage: t = ['(', 'a', '->', '~', 'c', ')']
sage: logicparser.tree_parse(t, polish = True)
['->', 'a', ['~', 'c']]
sage: r = ['(', '~', '~', 'a', '|', 'b', ')']
sage: logicparser.tree_parse(r, polish = True)
['|', ['~', ['~', 'a']], 'b']
```

```
>>> from sage.all import *
>>> import sage.logic.logicparser as logicparser
```

(continues on next page)

(continued from previous page)

```
>>> t = ['(', 'a', '->', '~', 'c', ')']
>>> logicparser.tree_parse(t, polish = True)
['->', 'a', ['~', 'c']]
>>> r = ['(', '~', '~', 'a', '|', 'b', ')']
>>> logicparser.tree_parse(r, polish = True)
['|', ['~', ['~', 'a']], 'b']
```

sage.logic.logicparser.**apply_func**(tree, func)

Apply func to each node of tree, and return a new parse tree.

INPUT:

- tree – a parse tree of a boolean formula
- func – a function to be applied to each node of tree; this may be a function that comes from elsewhere in the logic module

OUTPUT: the new parse tree in the form of a nested list

EXAMPLES:

This example uses `apply_func()` where func switches two entries of tree:

```
sage: import sage.logic.logicparser as logicparser
sage: t = ['|', ['&', 'a', 'b'], ['&', 'a', 'c']]
sage: f = lambda t: [t[0], t[2], t[1]]
sage: logicparser.apply_func(t, f)
['|', ['&', 'c', 'a'], ['&', 'b', 'a']]
```

```
>>> from sage.all import *
>>> import sage.logic.logicparser as logicparser
>>> t = ['|', ['&', 'a', 'b'], ['&', 'a', 'c']]
>>> f = lambda t: [t[Integer(0)], t[Integer(2)], t[Integer(1)]]
>>> logicparser.apply_func(t, f)
['|', ['&', 'c', 'a'], ['&', 'b', 'a']]
```

sage.logic.logicparser.**get_trees**(*statements)

Return the full syntax parse trees of the statements.

INPUT:

- *statements – strings or BooleanFormula instances

OUTPUT: the parse trees in a list

EXAMPLES:

This example illustrates finding the parse trees of multiple formulas.

```
sage: import sage.logic.propcalc as propcalc
sage: import sage.logic.logicparser as logicparser
sage: f = propcalc.formula("(a|b)&~~c")
sage: g = "a<->(~(c))"
sage: h = "~b"
sage: logicparser.get_trees(f, g, h)
[['&', ['|', 'a', 'b'], ['~', ['~', 'c']]],
 ['<->', 'a', ['~', 'c']],
 ['~', 'b']]
```

```
>>> from sage.all import *
>>> import sage.logic.propcalc as propcalc
>>> import sage.logic.logicparser as logicparser
>>> f = propcalc.formula("(a|b)&~~c")
>>> g = "a<->(~(c))"
>>> h = "~b"
>>> logicparser.get_trees(f, g, h)
[['&', ['|', 'a', 'b'], ['~', ['~', 'c']]],
 ['<->', 'a', ['~', 'c']],
 ['~', 'b']]
```

```
sage: i = "(~q->p)"
sage: j = propcalc.formula("a")
sage: logicparser.get_trees(i, j)
[['->', ['~', 'q'], 'p'], ['a']]
```

```
>>> from sage.all import *
>>> i = "(~q->p)"
>>> j = propcalc.formula("a")
>>> logicparser.get_trees(i, j)
[['->', ['~', 'q'], 'p'], ['a']]
```

```
sage: k = "p"
sage: logicparser.get_trees(k)
[['p']]
```

```
>>> from sage.all import *
>>> k = "p"
>>> logicparser.get_trees(k)
[['p']]
```

AUTHORS:

- Paul Scurek (2013-08-06)

`sage.logic.logicparser.parse(s)`

Return a parse tree from a boolean formula `s`.

INPUT:

- `s` – string containing a boolean formula

OUTPUT:

A list containing the parse tree and a list containing the variables in a boolean formula in this order:

1. the list containing the parse tree
2. the list containing the variables

EXAMPLES:

This example illustrates how to produce the parse tree of a boolean formula `s`:

```
sage: import sage.logic.logicparser as logicparser
sage: s = 'a|b&c'
```

(continues on next page)

(continued from previous page)

```
sage: t = logicparser.parse(s)
sage: t
(['|', 'a', ['&', 'b', 'c']], ['a', 'b', 'c'])
```

```
>>> from sage.all import *
>>> import sage.logic.logicparser as logicparser
>>> s = 'a|b&c'
>>> t = logicparser.parse(s)
>>> t
(['|', 'a', ['&', 'b', 'c']], ['a', 'b', 'c'])
```

sage.logic.logicparser.**parse_ltor**(toks, n=0, polish=False)

Return a parse tree from toks, where each token in toks is atomic.

INPUT:

- toks – list of tokens; each token is atomic
- n – integer (default: 0) representing which order of operations are occurring
- polish – boolean (default: False); when True, double negations are not cancelled and negated statements are turned into list of length two

OUTPUT: the parse tree as a nested list that depends on polish as follows:

- If False, then return a simplified parse tree.
- If True, then return the full syntax parse tree.

EXAMPLES:

This example illustrates the use of `parse_ltor()` when polish is False:

```
sage: import sage.logic.logicparser as logicparser
sage: t = ['a', '|', 'b', '&', 'c']
sage: logicparser.parse_ltor(t)
(['|', 'a', ['&', 'b', 'c']])
```

```
>>> from sage.all import *
>>> import sage.logic.logicparser as logicparser
>>> t = ['a', '|', 'b', '&', 'c']
>>> logicparser.parse_ltor(t)
(['|', 'a', ['&', 'b', 'c']])
```

```
sage: import sage.logic.logicparser as logicparser
sage: t = ['a', '->', '~', '~', 'b']
sage: logicparser.parse_ltor(t)
['->', 'a', 'b']
```

```
>>> from sage.all import *
>>> import sage.logic.logicparser as logicparser
>>> t = ['a', '->', '~', '~', 'b']
>>> logicparser.parse_ltor(t)
['->', 'a', 'b']
```

We now repeat the previous example, but with polish being True:

```
sage: import sage.logic.logicparser as logicparser
sage: t = ['a', '->', '~', '~', 'b']
sage: logicparser.parse_ltor(t, polish = True)
['->', 'a', ['~', ['~', 'b']]]
```

```
>>> from sage.all import *
>>> import sage.logic.logicparser as logicparser
>>> t = ['a', '->', '~', '~', 'b']
>>> logicparser.parse_ltor(t, polish = True)
['->', 'a', ['~', ['~', 'b']]]
```

sage.logic.logicparser.**polish_parse**(s)

Return the full syntax parse tree from a boolean formula s.

INPUT:

- s – string containing a boolean expression

OUTPUT: the full syntax parse tree as a nested list

EXAMPLES:

This example illustrates how to find the full syntax parse tree of a boolean formula:

```
sage: import sage.logic.logicparser as logicparser
sage: s = 'a|~~b'
sage: t = logicparser.polish_parse(s)
sage: t
['|', 'a', ['~', ['~', 'b']]]
```

```
>>> from sage.all import *
>>> import sage.logic.logicparser as logicparser
>>> s = 'a|~~b'
>>> t = logicparser.polish_parse(s)
>>> t
['|', 'a', ['~', ['~', 'b']]]
```

AUTHORS:

- Paul Scurek (2013-08-03)

sage.logic.logicparser.**prefix_to_infix**(prefix_tree)

Convert a parse tree from prefix form to infix form.

INPUT:

- prefix_tree – list; this is a full syntax parse tree in prefix form

OUTPUT: list containing the tree in infix form

EXAMPLES:

This example illustrates converting a prefix tree to an infix tree:

```
sage: import sage.logic.logicparser as logicparser
sage: import sage.logic.propcalc as propcalc
sage: t = ['|', ['~', 'a'], ['&', 'b', 'c']]
```

(continues on next page)

(continued from previous page)

```
sage: logicparser.prefix_to_infix(t)
[['~', 'a'], '|', ['b', '&', 'c']]
```

```
>>> from sage.all import *
>>> import sage.logic.logicparser as logicparser
>>> import sage.logic.propcalc as propcalc
>>> t = ['|', ['~', 'a'], ['&', 'b', 'c']]
>>> logicparser.prefix_to_infix(t)
[['~', 'a'], '|', ['b', '&', 'c']]
```

```
sage: f = propcalc.formula("(a&~b)<->~~~(c|d)")
sage: logicparser.prefix_to_infix(f.full_tree())
[['a', '&', ['~', 'b']], '<->', ['~', ['~', ['~', ['c', '|', 'd']]]]]]
```

```
>>> from sage.all import *
>>> f = propcalc.formula("(a&~b)<->~~~(c|d)")
>>> logicparser.prefix_to_infix(f.full_tree())
[['a', '&', ['~', 'b']], '<->', ['~', ['~', ['~', ['c', '|', 'd']]]]]]
```

Note

The function `polish_parse()` may be passed as an argument, but `tree_parse()` may not unless the parameter `polish` is set to `True`.

AUTHORS:

- Paul Scurek (2013-08-06)

`sage.logic.logicparser.recover_formula(prefix_tree)`

Recover the formula from a parse tree in prefix form.

INPUT:

- `prefix_tree` – list; this is a full syntax parse tree in prefix form

OUTPUT: the formula as a string

EXAMPLES:

This example illustrates the recovery of a formula from a parse tree:

```
sage: import sage.logic.propcalc as propcalc
sage: import sage.logic.logicparser as logicparser
sage: t = ['<->', ['&', 'a', ['~', ['~', 'c']]], ['~', '|', ['~', 'c'], 'd']]
sage: logicparser.recover_formula(t)
'(a&~~c)->~(c|d) '

sage: f = propcalc.formula("a&(~~c|d)")
sage: logicparser.recover_formula(f.full_tree())
'a&(~~c|d) '

sage: r = ['~', 'a']
sage: logicparser.recover_formula(r)
```

(continues on next page)

(continued from previous page)

```
'~a'

sage: s = ['d']
sage: logicparser.recover_formula(s)
'd'

>>> from sage.all import *
>>> import sage.logic.propcalc as propcalc
>>> import sage.logic.logicparser as logicparser
>>> t = ['->', ['&', 'a', ['~', ['~', 'c']]], ['~', ['|', ['~', 'c'], 'd']]]
>>> logicparser.recover_formula(t)
'(a&~~c)->~(c|d)'

>>> f = propcalc.formula("a&(~~c|d)")
>>> logicparser.recover_formula(f.full_tree())
'a&(~~c|d)'

>>> r = ['~', 'a']
>>> logicparser.recover_formula(r)
'~a'

>>> s = ['d']
>>> logicparser.recover_formula(s)
'd'
```

Note

The function `polish_parse()` may be passed as an argument, but `tree_parse()` may not unless the parameter `polish` is set to `True`.

AUTHORS:

- Paul Scurek (2013-08-06)

`sage.logic.logicparser.recover_formula_internal(prefix_tree)`

Recover the formula from a parse tree in prefix form.

INPUT:

- `prefix_tree` – list; this is a simple tree with at most one operator in prefix form

OUTPUT: the formula as a string

EXAMPLES:

This example illustrates recovering the formula from a parse tree:

```
sage: import sage.logic.logicparser as logicparser
sage: import sage.logic.propcalc as propcalc
sage: t = ['->', 'a', 'b']
sage: logicparser.recover_formula_internal(t)
'(a->b)'

sage: r = ['~', 'c']
```

(continues on next page)

(continued from previous page)

```
sage: logicparser.recover_formula_internal(r)
'~c'

sage: s = ['d']
sage: logicparser.recover_formula_internal(s)
'd'
```

```
>>> from sage.all import *
>>> import sage.logic.logicparser as logicparser
>>> import sage.logic.propcalc as propcalc
>>> t = ['->', 'a', 'b']
>>> logicparser.recover_formula_internal(t)
'(a->b) '

>>> r = ['~', 'c']
>>> logicparser.recover_formula_internal(r)
'~c'

>>> s = ['d']
>>> logicparser.recover_formula_internal(s)
'd'
```

We can pass `recover_formula_internal()` as an argument in `apply_func()`:

```
sage: f = propcalc.formula("~(d|c)<->(a&~~~c)")
sage: logicparser.apply_func(f.full_tree(), logicparser.recover_formula_internal)
' (~(d|c)<->(a&~~~c)) '
```

```
>>> from sage.all import *
>>> f = propcalc.formula("~(d|c)<->(a&~~~c)")
>>> logicparser.apply_func(f.full_tree(), logicparser.recover_formula_internal)
' (~(d|c)<->(a&~~~c)) '
```

Note

This function is for internal use by `logicparser`. The function recovers the formula of a simple parse tree in prefix form. A simple parse tree contains at most one operator.

The function `polish_parse()` may be passed as an argument, but `tree_parse()` may not unless the parameter `polish` is set to `True`.

AUTHORS:

- Paul Scurek (2013-08-06)

`sage.logic.logicparser.to_infix_internal(prefix_tree)`

Convert a simple parse tree from prefix form to infix form.

INPUT:

- `prefix_tree` – list; this is a simple parse tree in prefix form with at most one operator

OUTPUT: the tree in infix form as a list

EXAMPLES:

This example illustrates converting a simple tree from prefix to infix form:

```
sage: import sage.logic.logicparser as logicparser
sage: import sage.logic.propcalc as propcalc
sage: t = ['|', 'a', 'b']
sage: logicparser.to_infix_internal(t)
['a', '|', 'b']
```

```
>>> from sage.all import *
>>> import sage.logic.logicparser as logicparser
>>> import sage.logic.propcalc as propcalc
>>> t = ['|', 'a', 'b']
>>> logicparser.to_infix_internal(t)
['a', '|', 'b']
```

We can pass `to_infix_internal()` as an argument in `apply_func()`:

```
sage: f = propcalc.formula("(a&~b)<->~~~(c|d)")
sage: logicparser.apply_func(f.full_tree(), logicparser.to_infix_internal)
[['a', '&', ['~', 'b']], '<->', ['~', ['~', ['~', ['c', '|', 'd']]]]]
```

```
>>> from sage.all import *
>>> f = propcalc.formula("(a&~b)<->~~~(c|d)")
>>> logicparser.apply_func(f.full_tree(), logicparser.to_infix_internal)
[['a', '&', ['~', 'b']], '<->', ['~', ['~', ['~', ['c', '|', 'd']]]]]
```

Note

This function is for internal use by `logicparser`. It converts a simple parse tree from prefix form to infix form. A simple parse tree contains at most one operator.

The function `polish_parse()` may be passed as an argument, but `tree_parse()` may not unless the parameter `polish` is set to `True`.

AUTHORS:

- Paul Scurek (2013-08-06)

`sage.logic.logicparser.tokenize(s)`

Return the tokens and the distinct variables appearing in a boolean formula `s`.

INPUT:

- `s` – string representation of a boolean formula

OUTPUT:

The tokens and variables as an ordered pair of lists in the following order:

1. A list containing the tokens of `s`, in the order they appear in `s`
2. A list containing the distinct variables in `s`, in the order they appear in `s`

EXAMPLES:

This example illustrates how to tokenize a string representation of a boolean formula:

```
sage: import sage.logic.logicparser as logicparser
sage: s = 'a|b&c'
sage: t = logicparser.tokenize(s)
sage: t
(['(', 'a', '|', 'b', '&', 'c', ')'], ['a', 'b', 'c'])
```

```
>>> from sage.all import *
>>> import sage.logic.logicparser as logicparser
>>> s = 'a|b&c'
>>> t = logicparser.tokenize(s)
>>> t
(['(', 'a', '|', 'b', '&', 'c', ')'], ['a', 'b', 'c'])
```

sage.logic.logicparser.**tree_parse**(toks, polish=False)

Return a parse tree from the tokens in toks.

INPUT:

- toks – list of tokens from a boolean formula
- polish – boolean (default: False); when True, *tree_parse()* will return the full syntax parse tree

OUTPUT:

A parse tree in the form of a nested list that depends on polish as follows:

- If False, then return a simplified parse tree.
- If True, then return the full syntax parse tree.

EXAMPLES:

This example illustrates the use of *tree_parse()* when polish is False:

```
sage: import sage.logic.logicparser as logicparser
sage: t = ['(', 'a', '|', 'b', '&', 'c', ')']
sage: logicparser.tree_parse(t)
['|', 'a', ['&', 'b', 'c']]
```

```
>>> from sage.all import *
>>> import sage.logic.logicparser as logicparser
>>> t = ['(', 'a', '|', 'b', '&', 'c', ')']
>>> logicparser.tree_parse(t)
['|', 'a', ['&', 'b', 'c']]
```

We now demonstrate the use of *tree_parse()* when polish is True:

```
sage: t = ['(', 'a', '->', '~', '~', 'b', ')']
sage: logicparser.tree_parse(t)
['->', 'a', 'b']
sage: t = ['(', 'a', '->', '~', '~', 'b', ')']
sage: logicparser.tree_parse(t, polish = True)
['->', 'a', ['~', ['~', 'b']]]
```

```
>>> from sage.all import *
>>> t = ['(', 'a', '->', '~', '~', 'b', ')']
```

(continues on next page)

(continued from previous page)

```
>>> logicparser.tree_parse(t)
['->', 'a', 'b']
>>> t = ['(', 'a', '->', '~', '~', 'b', ')']
>>> logicparser.tree_parse(t, polish = True)
['->', 'a', ['~', ['~', 'b']]]
```

SYMBOLIC LOGIC EXPRESSIONS

An expression is created from a string that consists of the operators `!`, `&`, `|`, `->`, `<->`, which correspond to the logical functions not, and, or, if then, if and only if, respectively. Variable names must start with a letter and contain only alpha-numeric and the underscore character.

AUTHORS:

- Chris Gorecki (2007): initial version
- William Stein (2007-08-31): integration into Sage 2.8.4
- Paul Scurek (2013-08-03): updated docstring formatting

class sage.logic.logic.SymbolicLogic

Bases: object

EXAMPLES:

This example illustrates how to create a boolean formula and print its table:

```
sage: log = SymbolicLogic()
sage: s = log.statement("a&b|!(c|a)")
sage: t = log.truthtable(s)
sage: log.print_table(t)
```

a	b	c	value
False	False	False	True
False	False	True	False
False	True	False	True
False	True	True	False
True	False	False	False
True	False	True	False
True	True	False	True
True	True	True	True

```
>>> from sage.all import *
>>> log = SymbolicLogic()
>>> s = log.statement("a&b|!(c|a)")
>>> t = log.truthtable(s)
>>> log.print_table(t)
```

a	b	c	value
False	False	False	True
False	False	True	False

(continues on next page)

(continued from previous page)

False	True	False	True
False	True	True	False
True	False	False	False
True	False	True	False
True	True	False	True
True	True	True	True

combine (*statement1*, *statement2*)

Return a new statement which contains the two statements or'd together.

INPUT:

- *statement1* – the first statement
- *statement2* – the second statement

OUTPUT: a new statement which or'd the given statements together

EXAMPLES:

```
sage: log = SymbolicLogic()
sage: s1 = log.statement("(a&b)")
sage: s2 = log.statement("b")
sage: log.combine(s1,s2)
[['OPAREN',
  'OPAREN',
  'OPAREN',
  'a',
  'AND',
  'b',
  'CPAREN',
  'CPAREN',
  'OR',
  'OPAREN',
  'b',
  'CPAREN',
  'CPAREN'],
 {'a': 'False', 'b': 'False'},
 ['a', 'b', 'b']]
```

```
>>> from sage.all import *
>>> log = SymbolicLogic()
>>> s1 = log.statement("(a&b)")
>>> s2 = log.statement("b")
>>> log.combine(s1,s2)
[['OPAREN',
  'OPAREN',
  'OPAREN',
  'a',
  'AND',
  'b',
  'CPAREN',
  'CPAREN',
  'OR',
```

(continues on next page)

(continued from previous page)

```
'OPAREN',
'b',
'CPAREN',
'CPAREN'],
{'a': 'False', 'b': 'False'},
['a', 'b', 'b']]
```

print_table(table)

Return a truthtable corresponding to the given statement.

INPUT:

- table – object created by `truthtable()` method; it contains the variable values and the evaluation of the statement

OUTPUT: a formatted version of the truth table

EXAMPLES:

This example illustrates the creation of a statement and its truth table:

```
sage: log = SymbolicLogic()
sage: s = log.statement("a&b|!(c|a)")
sage: t = log.truthtable(s) #creates the whole truth table
sage: log.print_table(t)
```

a	b	c	value
False	False	False	True
False	False	True	False
False	True	False	True
False	True	True	False
True	False	False	False
True	False	True	False
True	True	False	True
True	True	True	True

```
>>> from sage.all import *
>>> log = SymbolicLogic()
>>> s = log.statement("a&b|!(c|a)")
>>> t = log.truthtable(s) #creates the whole truth table
>>> log.print_table(t)
```

a	b	c	value
False	False	False	True
False	False	True	False
False	True	False	True
False	True	True	False
True	False	False	False
True	False	True	False
True	True	False	True
True	True	True	True

We can also print a shortened table:

```
sage: t = log.truthtable(s, 1, 5)
sage: log.print_table(t)
a      | b      | c      | value |
-----|-----|-----|-----|
False  | False  | True   | False |
False  | True   | False  | True  |
False  | True   | True   | False |
True   | False  | False  | False |
```

```
>>> from sage.all import *
>>> t = log.truthtable(s, Integer(1), Integer(5))
>>> log.print_table(t)
a      | b      | c      | value |
-----|-----|-----|-----|
False  | False  | True   | False |
False  | True   | False  | True  |
False  | True   | True   | False |
True   | False  | False  | False |
```

prove (*statement*)

A function to test to see if the statement is a tautology or contradiction by calling a C++ library.

Todo

Implement this method.

EXAMPLES:

```
sage: log = SymbolicLogic()
sage: s = log.statement("a&b|!(c|a)")
sage: log.prove(s)
Traceback (most recent call last):
...
NotImplementedError
```

```
>>> from sage.all import *
>>> log = SymbolicLogic()
>>> s = log.statement("a&b|!(c|a)")
>>> log.prove(s)
Traceback (most recent call last):
...
NotImplementedError
```

simplify (*table*)

Call a C++ implementation of the ESPRESSO algorithm to simplify the given truth table.

Todo

Implement this method.

EXAMPLES:

```
sage: log = SymbolicLogic()
sage: s = log.statement("a&b|!(c|a)")
sage: t = log.truthtable(s)
sage: log.simplify(t)
Traceback (most recent call last):
...
NotImplementedError
```

```
>>> from sage.all import *
>>> log = SymbolicLogic()
>>> s = log.statement("a&b|!(c|a)")
>>> t = log.truthtable(s)
>>> log.simplify(t)
Traceback (most recent call last):
...
NotImplementedError
```

statement (*s*)

Return a token list to be used by other functions in the class.

INPUT:

- *s* – string containing the logic expression to be manipulated
- *global_vars* – dictionary with variable names as keys and the variables' current boolean values as dictionary values
- *global_vars_order* – list of the variables in the order that they are found

OUTPUT: list of length three containing the following in this order:

1. a list of tokens
2. a dictionary of variable/value pairs
3. a list of the variables in the order they were found

EXAMPLES:

This example illustrates the creation of a statement:

```
sage: log = SymbolicLogic()
sage: s = log.statement("a&b|!(c|a)")
sage: s2 = log.statement("!(!(a&b))")
```

```
>>> from sage.all import *
>>> log = SymbolicLogic()
>>> s = log.statement("a&b|!(c|a)")
>>> s2 = log.statement("!(!(a&b))")
```

It is an error to use invalid variable names:

```
sage: s = log.statement("3fe & @q")
Invalid variable name: 3fe
Invalid variable name: @q
```

```
>>> from sage.all import *
>>> s = log.statement("3fe & @q")
Invalid variable name: 3fe
Invalid variable name: @q
```

It is also an error to use invalid syntax:

```
sage: s = log.statement("a&&b")
Malformed Statement
sage: s = log.statement("a&(b)")
Malformed Statement
```

```
>>> from sage.all import *
>>> s = log.statement("a&&b")
Malformed Statement
>>> s = log.statement("a&(b)")
Malformed Statement
```

truthtable (*statement*, *start*=0, *end*=-1)

Return a truth table.

INPUT:

- *statement* – list; it contains the tokens and the two global variables *vars* and *vars_order*
- *start* – integer (default: 0); this represents the row of the truth table from which to start
- *end* – integer (default: -1); this represents the last row of the truth table to be created

OUTPUT:

The truth table as a 2d array with the creating formula tacked to the front.

EXAMPLES:

This example illustrates the creation of a statement:

```
sage: log = SymbolicLogic()
sage: s = log.statement("a&b|!(c|a)")
sage: t = log.truthtable(s) #creates the whole truth table
```

```
>>> from sage.all import *
>>> log = SymbolicLogic()
>>> s = log.statement("a&b|!(c|a)")
>>> t = log.truthtable(s) #creates the whole truth table
```

We can now create truthtable of rows 1 to 5:

```
sage: s2 = log.truthtable(s, 1, 5); s2
[[['OPAREN',
  'a',
  'AND',
  'b',
  'OR',
  'NOT',
  'OPAREN',
```

(continues on next page)

(continued from previous page)

```

    'c',
    'OR',
    'a',
    'CPAREN',
    'CPAREN'],
    {'a': 'True', 'b': 'False', 'c': 'False'},
    ['a', 'b', 'c']],
    ['False', 'False', 'True', 'False'],
    ['False', 'True', 'False', 'True'],
    ['False', 'True', 'True', 'False'],
    ['True', 'False', 'False', 'False']]

```

```

>>> from sage.all import *
>>> s2 = log.truthtable(s, Integer(1), Integer(5)); s2
[[['OPAREN',
    'a',
    'AND',
    'b',
    'OR',
    'NOT',
    'OPAREN',
    'c',
    'OR',
    'a',
    'CPAREN',
    'CPAREN'],
    {'a': 'True', 'b': 'False', 'c': 'False'},
    ['a', 'b', 'c']],
    ['False', 'False', 'True', 'False'],
    ['False', 'True', 'False', 'True'],
    ['False', 'True', 'True', 'False'],
    ['True', 'False', 'False', 'False']]

```

Note

When sent with no start or end parameters this is an exponential time function requiring $O(2^n)$ time, where n is the number of variables in the logic expression

`sage.logic.logic.eval(toks)`

Evaluate the expression contained in *toks*.

INPUT:

- *toks* – list of tokens; this represents a boolean expression

OUTPUT: a boolean value to be determined as follows:

- True if expression evaluates to True.
- False if expression evaluates to False.

Note

This function is for internal use by the *SymbolicLogic* class. The evaluations rely on setting the values of the variables in the global dictionary vars.

`sage.logic.logic.eval_and_op(lval, rval)`

Apply the 'and' operator to `lval` and `rval`.

INPUT:

- `lval` – string; this represents the value of the variable appearing to the left of the 'and' operator
- `rval` – string; this represents the value of the variable appearing to the right of the 'and' operator

OUTPUT: the result of applying 'and' to `lval` and `rval` as a string

Note

This function is for internal use by the *SymbolicLogic* class.

`sage.logic.logic.eval_bin_op(args)`

Return a boolean value based on the truth table of the operator in `args`.

INPUT:

- `args` – list of length 3; this contains a variable name, then a binary operator, and then a variable name, in that order

OUTPUT:

A boolean value; this is the evaluation of the operator based on the truth values of the variables.

Note

This function is for internal use by the *SymbolicLogic* class.

`sage.logic.logic.eval_iff_op(lval, rval)`

Apply the 'if and only if' operator to `lval` and `rval`.

INPUT:

- `lval` – string; this represents the value of the variable appearing to the left of the 'if and only if' operator
- `rval` – string; this represents the value of the variable appearing to the right of the 'if and only if' operator

OUTPUT:

A string representing the result of applying 'if and only if' to `lval` and `rval`.

Note

This function is for internal use by the *SymbolicLogic* class.

`sage.logic.logic.eval_ifthen_op(lval, rval)`

Apply the 'if then' operator to `lval` and `rval`.

INPUT:

- `lval` – string; this represents the value of the variable appearing to the left of the 'if then' operator
- `rval` – string; this represents the value of the variable appearing to the right of the 'if then' operator

OUTPUT:

A string representing the result of applying 'if then' to `lval` and `rval`.

Note

This function is for internal use by the *SymbolicLogic* class.

`sage.logic.logic.eval_ltor_toks(lrtoks)`

Evaluates the expression contained in `lrtoks`.

INPUT:

- `lrtoks` – list of tokens; this represents a part of a boolean formula that contains no inner parentheses

OUTPUT: a boolean value to be determined as follows:

- True if expression evaluates to True.
- False if expression evaluates to False.

Note

This function is for internal use by the *SymbolicLogic* class. The evaluations rely on setting the values of the variables in the global dictionary vars.

`sage.logic.logic.eval_mon_op(args)`

Return a boolean value based on the truth table of the operator in `args`.

INPUT:

- `args` – list of length 2; this contains the token 'NOT' and then a variable name

OUTPUT: a boolean value to be determined as follows:

- True if the variable in `args` is False.
- False if the variable in `args` is True.

Note

This function is for internal use by the *SymbolicLogic* class.

`sage.logic.logic.eval_or_op(lval, rval)`

Apply the 'or' operator to `lval` and `rval`.

INPUT:

- `lval` – string; this represents the value of the variable appearing to the left of the 'or' operator

- `rval` – string; this represents the value of the variable appearing to the right of the ‘or’ operator

OUTPUT: string representing the result of applying ‘or’ to `lval` and `rval`

Note

This function is for internal use by the *SymbolicLogic* class.

`sage.logic.logic.get_bit(x, c)`

Determine if bit `c` of the number `x` is 1.

INPUT:

- `x` – integer; this is the number from which to take the bit
- `c` – integer; this is the bit number to be taken

OUTPUT: a boolean value to be determined as follows:

- True if bit `c` of `x` is 1.
- False if bit `c` of `x` is not 1.

Note

This function is for internal use by the *SymbolicLogic* class.

EXAMPLES:

```
sage: from sage.logic.logic import get_bit
sage: get_bit(int(2), int(1))
'True'
sage: get_bit(int(8), int(0))
'False'
```

```
>>> from sage.all import *
>>> from sage.logic.logic import get_bit
>>> get_bit(int(Integer(2)), int(Integer(1)))
'True'
>>> get_bit(int(Integer(8)), int(Integer(0)))
'False'
```

`sage.logic.logic.reduce_bins(lrtoks)`

Evaluate `lrtoks` to a single boolean value.

INPUT:

- `lrtoks` – list of tokens; this represents a part of a boolean formula that contains no inner parentheses or monotonic operators

OUTPUT:

None; the pointer to `lrtoks` is now a list containing True or False.

Note

This function is for internal use by the *SymbolicLogic* class.

`sage.logic.logic.reduce_monos(lrtoks)`

Replace monotonic operator/variable pairs with a boolean value.

INPUT:

- `lrtoks` – list of tokens; this represents a part of a boolean expression that contains now inner parentheses

OUTPUT:

None; the pointer to `lrtoks` is now a list containing monotonic operators.

Note

This function is for internal use by the *SymbolicLogic* class.

`sage.logic.logic.tokenize(s, toks)`

Tokenize `s` and place the tokens of `s` in `toks`.

INPUT:

- `s` – string; this contains a boolean expression
- `toks` – list; this will be populated with the tokens of `s`

OUTPUT: none; the tokens of `s` are placed in `toks`

Note

This function is for internal use by the *SymbolicLogic* class.

EXAMPLES:

```
sage: from sage.logic.logic import tokenize
sage: toks = []
sage: tokenize("(a&b)|c", toks)
sage: toks
['OPAREN', 'a', 'AND', 'b', 'CPAREN', 'OR', 'c', 'CPAREN']
```

```
>>> from sage.all import *
>>> from sage.logic.logic import tokenize
>>> toks = []
>>> tokenize("(a&b)|c", toks)
>>> toks
['OPAREN', 'a', 'AND', 'b', 'CPAREN', 'OR', 'c', 'CPAREN']
```


LOGIC TABLES

A logic table is essentially a 2-D array that is created by the statement class and stored in the private global variable table, along with a list containing the variable names to be used, in order.

The order in which the table is listed essentially amounts to counting in binary. For instance, with the variables *A*, *B*, and *C* the truth table looks like:

A	B	C	value
False	False	False	?
False	False	True	?
False	True	False	?
False	True	True	?
True	False	False	?
True	False	True	?
True	True	False	?
True	True	True	?

This is equivalent to counting in binary, where a table would appear thus;

2 ²	2 ¹	2 ⁰	value
0	0	0	0
0	0	1	1
0	1	0	2
0	1	1	3
1	0	0	4
1	0	1	5
1	1	0	6
1	1	1	7

Given that a table can be created corresponding to any range of acceptable values for a given statement, it is easy to find the value of a statement for arbitrary values of its variables.

AUTHORS:

- William Stein (2006): initial version
- Chris Gorecki (2006): initial version
- Paul Scurek (2013-08-03): updated docstring formatting

EXAMPLES:

Create a truth table of a boolean formula:

```
sage: import sage.logic.propcalc as propcalc
sage: s = propcalc.formula("a&b|~(c|a)")
sage: s.truthtable()
a      b      c      value
False  False  False  True
False  False  True   False
False  True   False  True
False  True   True   False
True   False  False  False
True   False  True   False
True   True   False  True
True   True   True   True
```

```
>>> from sage.all import *
>>> import sage.logic.propcalc as propcalc
>>> s = propcalc.formula("a&b|~(c|a)")
>>> s.truthtable()
a      b      c      value
False  False  False  True
False  False  True   False
False  True   False  True
False  True   True   False
True   False  False  False
True   False  True   False
True   True   False  True
True   True   True   True
```

Get the LaTeX code for a truth table:

```
sage: latex(s.truthtable(5,11))
\\begin{tabular}{llll}c & b & a & value \\\\hline True & False & True & False \\True &
↪ True & False & True \\True & True & True & True\\end{tabular}
```

```
>>> from sage.all import *
>>> latex(s.truthtable(Integer(5),Integer(11)))
\\begin{tabular}{llll}c & b & a & value \\\\hline True & False & True & False \\True &
↪ True & False & True \\True & True & True & True\\end{tabular}
```

It is not an error to use nonsensical numeric inputs:

```
sage: s = propcalc.formula("a&b|~(c|a)")
sage: s.truthtable(5, 9)
a      b      c      value
True   False  True   False
True   True   False  True
True   True   True   True

sage: s.truthtable(9, 5)
a      b      c      value
```

```
>>> from sage.all import *
>>> s = propcalc.formula("a&b|~(c|a)")
```

(continues on next page)

(continued from previous page)

```
>>> s.truthtable(Integer(5), Integer(9))
a      b      c      value
True   False  True   False
True   True   False  True
True   True   True   True

>>> s.truthtable(Integer(9), Integer(5))
a      b      c      value
```

If one argument is provided, truthtable defaults to the end:

```
sage: s.truthtable(-1)
a      b      c      value
False  False  False  True
False  False  True   False
False  True   False  True
False  True   True   False
True   False  False  False
True   False  True   False
True   True   False  True
True   True   True   True
```

```
>>> from sage.all import *
>>> s.truthtable(-Integer(1))
a      b      c      value
False  False  False  True
False  False  True   False
False  True   False  True
False  True   True   False
True   False  False  False
True   False  True   False
True   True   False  True
True   True   True   True
```

If the second argument is negative, truthtable defaults to the end:

```
sage: s.truthtable(4, -2)
a      b      c      value
True   False  False  False
True   False  True   False
True   True   False  True
True   True   True   True
```

```
>>> from sage.all import *
>>> s.truthtable(Integer(4), -Integer(2))
a      b      c      value
True   False  False  False
True   False  True   False
True   True   False  True
True   True   True   True
```

Note

For statements that contain a variable list that when printed is longer than the latex page, the columns of the table will run off the screen.

class sage.logic.logictable.**Truthtable**(*t*, *vo*)

Bases: object

A truth table.

INPUT:

- *t* – a 2-D array containing the table values
- *vo* – list of the variables in the expression in order, with each variable occurring only once

get_table_list()

Return a list representation of the calling table object.

OUTPUT: list representation of the table

EXAMPLES:

This example illustrates how to show the table as a list:

```
sage: import sage.logic.propcalc as propcalc
sage: s = propcalc.formula("man->monkey&human")
sage: s.truthtable().get_table_list()
[['man', 'monkey', 'human'], [False, False, False, True], [False, False, ↵
↵True, True], [False, True, False, True], [False, True, True, True], [True, ↵
↵False, False, False], [True, False, True, False], [True, True, False, ↵
↵False], [True, True, True, True]]
```

```
>>> from sage.all import *
>>> import sage.logic.propcalc as propcalc
>>> s = propcalc.formula("man->monkey&human")
>>> s.truthtable().get_table_list()
[['man', 'monkey', 'human'], [False, False, False, True], [False, False, ↵
↵True, True], [False, True, False, True], [False, True, True, True], [True, ↵
↵False, False, False], [True, False, True, False], [True, True, False, ↵
↵False], [True, True, True, True]]
```

INDICES AND TABLES

- [Index](#)
- [Module Index](#)
- [Search Page](#)

PYTHON MODULE INDEX

I

- `sage.logic.booleval`, 35
- `sage.logic.boolformula`, 9
- `sage.logic.logic`, 51
- `sage.logic.logicparser`, 39
- `sage.logic.logictable`, 63
- `sage.logic.propcalc`, 1

A

`add_statement()` (*sage.logic.boolformula.BooleanFormula method*), 13
`apply_func()` (*in module sage.logic.logicparser*), 41

B

`BooleanFormula` (*class in sage.logic.boolformula*), 13

C

`combine()` (*sage.logic.logic.SymbolicLogic method*), 52
`consistent()` (*in module sage.logic.propcalc*), 5
`convert_cnf()` (*sage.logic.boolformula.BooleanFormula method*), 14
`convert_cnf_recur()` (*sage.logic.boolformula.BooleanFormula method*), 14
`convert_cnf_table()` (*sage.logic.boolformula.BooleanFormula method*), 15
`convert_expression()` (*sage.logic.boolformula.BooleanFormula method*), 16
`convert_opt()` (*sage.logic.boolformula.BooleanFormula method*), 16

D

`dist_not()` (*sage.logic.boolformula.BooleanFormula method*), 17
`dist_ors()` (*sage.logic.boolformula.BooleanFormula method*), 17

E

`equivalent()` (*sage.logic.boolformula.BooleanFormula method*), 18
`eval()` (*in module sage.logic.logic*), 57
`eval_and_op()` (*in module sage.logic.logic*), 58
`eval_bin_op()` (*in module sage.logic.logic*), 58
`eval_f()` (*in module sage.logic.booleval*), 35
`eval_formula()` (*in module sage.logic.booleval*), 36
`eval_iff_op()` (*in module sage.logic.logic*), 58
`eval_ifthen_op()` (*in module sage.logic.logic*), 58
`eval_ltor_toks()` (*in module sage.logic.logic*), 59
`eval_mon_op()` (*in module sage.logic.logic*), 59
`eval_op()` (*in module sage.logic.booleval*), 37

`eval_or_op()` (*in module sage.logic.logic*), 59
`evaluate()` (*sage.logic.boolformula.BooleanFormula method*), 19

F

`formula()` (*in module sage.logic.propcalc*), 6
`full_tree()` (*sage.logic.boolformula.BooleanFormula method*), 19

G

`get_bit()` (*in module sage.logic.logic*), 60
`get_bit()` (*sage.logic.boolformula.BooleanFormula method*), 20
`get_formulas()` (*in module sage.logic.propcalc*), 6
`get_next_op()` (*sage.logic.boolformula.BooleanFormula method*), 21
`get_table_list()` (*sage.logic.logictable.Truthtable method*), 66
`get_trees()` (*in module sage.logic.logicparser*), 41

I

`iff()` (*sage.logic.boolformula.BooleanFormula method*), 22
`ifthen()` (*sage.logic.boolformula.BooleanFormula method*), 22
`implies()` (*sage.logic.boolformula.BooleanFormula method*), 23
`is_consequence()` (*in module sage.logic.boolformula*), 33
`is_consequence()` (*sage.logic.boolformula.BooleanFormula method*), 24
`is_contradiction()` (*sage.logic.boolformula.BooleanFormula method*), 25
`is_satisfiable()` (*sage.logic.boolformula.BooleanFormula method*), 26
`is_tautology()` (*sage.logic.boolformula.BooleanFormula method*), 26

L

`length()` (*sage.logic.boolformula.BooleanFormula method*), 27

M

module

sage.logic.booleval, 35
sage.logic.boolformula, 9
sage.logic.logic, 51
sage.logic.logicparser, 39
sage.logic.logictable, 63
sage.logic.propcalc, 1

P

parse() (in module sage.logic.logicparser), 42
parse_ltor() (in module sage.logic.logicparser), 43
polish_notation() (sage.logic.boolformula.Boolean-
Formula method), 28
polish_parse() (in module sage.logic.logicparser), 44
prefix_to_infix() (in module sage.logic.logicparser),
44
print_table() (sage.logic.logic.SymbolicLogic method),
53
prove() (sage.logic.logic.SymbolicLogic method), 54

R

recover_formula() (in module sage.logic.logicparser),
45
recover_formula_internal() (in module
sage.logic.logicparser), 46
reduce_bins() (in module sage.logic.logic), 60
reduce_monos() (in module sage.logic.logic), 61
reduce_op() (sage.logic.boolformula.BooleanFormula
method), 29

S

sage.logic.booleval
module, 35
sage.logic.boolformula
module, 9
sage.logic.logic
module, 51
sage.logic.logicparser
module, 39
sage.logic.logictable
module, 63
sage.logic.propcalc
module, 1
satformat() (sage.logic.boolformula.BooleanFormula
method), 29
simplify() (sage.logic.logic.SymbolicLogic method), 54
statement() (sage.logic.logic.SymbolicLogic method), 55
SymbolicLogic (class in sage.logic.logic), 51

T

to_infix() (sage.logic.boolformula.BooleanFormula
method), 30

to_infix_internal() (in module sage.logic.logic-
parser), 47
tokenize() (in module sage.logic.logic), 61
tokenize() (in module sage.logic.logicparser), 48
tree() (sage.logic.boolformula.BooleanFormula method),
31
tree_parse() (in module sage.logic.logicparser), 49
Truthtable (class in sage.logic.logictable), 66
truthtable() (sage.logic.boolformula.BooleanFormula
method), 31
truthtable() (sage.logic.logic.SymbolicLogic method),
56